

Sacramento28 Plank 413 & Tile 414 Extra Heavy Commerical Traffic



Size

Plank 4" x 36"
3 mm thick

Tile 18" x 18"
3 mm thick

Wear Layer

28 mil / UV-Cured Urethane

Edge Treatment

Square Edge

Installation

Full Spread Adhesive
Recommended Adhesive: NEXT 1200™

Product Classification

ASTM F1700 Class III, Type B

Coordinating Moldings

See nextfloor.net for more details.

Packaging

Plank 36 pieces per carton (45 lbs)
36 SF per carton
52 cartons per pallet

Tile 16 pieces per carton (45 lbs)
36 SF per carton
52 cartons per pallet

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passes>0.6
Static Load Limit	ASTM F970	1300 lbs
Sound Transmission Class (STC)	ASTM E492	64
Impact Isulation Class (IIC)	ASTM E989	69
High Frequency Impact Isulation Class(HIIC)	ASTM E3222	89
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		



Warranties

Lifetime Residential Wear
30-Year Commercial Wear

See full warranty text at nextfloor.net

Sample SKUs

Strap Sets

SS413NF
5 per carton (20 lbs)

Folders

3P413/414NF
20 per carton (64 lbs)