



canadiana

Northern Woods

VINYL FLOOR COVERING / PLANKS
REVÊTEMENT DE SOL DE VINYL / LATTES



Northern Woods incorporates the '3L Triple Lock (one piece drop-lock system)' that allows for an easier floating installation. Northern Woods has a double UV enhanced polyurethane coating, offers superior dimensional stability, acoustical properties and is FloorScore certified.

Northern Woods intègre le système breveté «Drop Lock Installation System» qui permet une installation flottante plus facile grâce à une technologie de verrouillage novatrice. Northern Woods possède une double couche de polyuréthane résistante aux UV et offre une stabilité dimensionnelle supérieure ainsi que des propriétés acoustiques. Certifié FloorScore.

canadiana

NORTHERN WOODS

DESCRIPTION	
 Total Thickness / Épaisseur	0.2165" (5.5 mm)
 Sizes / Dimensions	7" x 48" (182 x 1240 mm)
 Wear Layer / Couche d'usure	0.3 mm = 12 mil
Surface Finish / Protection	Double UV - Enhanced Polyurethane Coating Double couche de polyuréthane résistante aux UV
Care / Entretien	No harsh cleaners or amonia based cleaners. No wax. Double couche de polyuréthane résistante aux UV
Core / Masse	4 mm PVC resin and limestone / 4 mm résine de PVC et calcaire
Density / Densité	1980 kg / 33+ 5%
Bevel / Biseau	Micro bevelled edge / Coin micro-biseauté
Attached Backing / Endos	1.5 mm embossed EVA / Relief EVA 1.5mm
Embossing / Relief	Random EIR / EIR aléatoire
Installation / Installation	Floating / Flottant
Limited Warranty / Garantie limitée	25 year residential, 10 year commercial Résidentiel: 25 ans / commercial: 10 ans
PERFORMANCE	
STC - IIC Rating / Niveau de STC - IIC	67 STC - 73 IIC
Lock System / Système de verrouillage	3L Triple Lock (one piece drop-lock system) 3L Triple Lock (système de verrouillage en un morceau)
Under Floor Heating / Température du sous-plancher	Not to exceed 85°F (30°C) / Ne doit pas dépasser 30°C
 Static Load Resistance / Résistance au poinçonnement	ASTM F970 - 1950 PSI
ASTM / ASTM	F1700 Class III Type B
 Chemical + Stain Resistance / Résistance chimique et aux taches	ASTM F925 / NALAFa LF01-2011
 Slip Resistance / Résistance au glissement	ASTM D2047 0.39 Dry - 0.9 Wet
 Wheel Castor Resistance / Résistance chaise à roulettes	ISO 4918
 Dimensional Stability / Stabilité dimensionnelle	EN ISO23999:2012
 Flame Spread + Smoke Development / Propagation des flammes et dégagement de fumée	ASTM E648/662
ENVIRONMENTAL	
 Indoor Air Quality / VOC emission Qualité de l'air intérieur, émissions VOC	Phthalate Free / Sans Phthalate Compliant with FloorScore Requirements / Répond aux exigences FloorScore
 Recycling / Recyclage	100% Recyclable

Vancouver

4616 Canada Way
Burnaby, Vancouver BC
t +1 (604) 298 8453

Calgary

7360-12 Street S.E
Calgary, Alberta
t +1 (403) 259 0106

Edmonton

11141 184 Street
Edmonton, Alberta
t +1 (780) 454 8591

Windsor

3155 County Road #42
Windsor, Ontario
t +1 (519) 966 3580

London

993 Adelaide Street S.
London, Ontario
t +1 (519) 681 1961

Hamilton

140 Nebo Road
Hamilton, Ontario
t +1 (905) 383 5100

Toronto

950 Lawrence Ave W.
Toronto, Ontario
t +1 (416) 785 5151

Peterborough

774 Rye Street
Peterborough, Ontario
t +1 (705) 743 2881

Ottawa

1070 Morrison Drive
Ottawa, Ontario
t +1 (613) 820 6622

Montréal

5885 ch.de la Côte-de-Liesse
Ville St-Laurent, Québec
t +1 (514) 336 4311

Québec

2850, rue Jean-Perrin
Québec, Québec
t +1 (418) 653 5267

Moncton

555 Edinburgh Drive
Moncton, New Brunswick
t +1 (506) 853 0123

Halifax

66 Wright Ave.
Dartmouth, Halifax N.S.,
t +1 (902) 468 7679

St. John's

2 Bruce Street
Mount Pearl, St. John's Nfld
t +1 (709) 579 4600