



HRG
HERALGI


Picket
Collection

Picket

Collection

Innovadora y peculiar, pero sin dejar de lado su carácter natural y sencillo, es como describimos en HRG a la colección Picket. Nos encanta arriesgar dentro de los estilos más austeros, por lo que Picket ofrece configuraciones a nivel de colocación muy dispares en cuanto a orientación y mezcla de tonalidades.

It is innovative and peculiar, without forgetting its natural and simple character. That is how we define Picket collection. We love being risky inside the most austere styles. In this point, Picket offers very different fittings in terms of orientation and colour mixing.





Picket



Pasta Blanca / White Body Brillo /Gloss
7,5x23cm / 3"x9" ▼

Pasta Blanca / White Body Brillo /Gloss
1,4x23cm / 1/2"x9" ▼

Picket Quartino P1



Pasta Blanca / White Body Brillo /Gloss
2x23cm / 3/4"x9" ▼

Picket Pencil P1




Pasta Blanca / White Body Brillo /Gloss
7,5x23cm / 3"x9" ▼

Picket Field Tile G6



Colores/Coulores



Quartz



Beryl



Moonstone



Hematite

Picket Wall G11



Picket Frame G11



Pasta Blanca / White Body Brillo /Gloss
3,7x3,7cm / 1 1/2"x1 1/2" ▼

Picket Frame Start P2



Picket Start P2



Picket





 Picket Frame {Pg.5}, Picket wall {Pg.5}

Picket Frame {Pg.5}








Picket

Picket Frame {Pg.5}



Picket Frame {Pg.5}, Picket Wall {Pg.5}



Picket

Colección innovadora sin olvidar su carácter natural y simple
Innovative collection without forgetting its natural and simple character

Picket wall {Pg.5}, Picket Frame {Pg.5}, Quartino {Pg.4}, Pencil {Pg.4}



Picket



Picket wall {Pg.5}




Picket wall {Pg.5}



Picket

Picket Wall {Pg.5}, Picket Frame {Pg.5}, Picket Field Tile {Pg.4}, Pencil {Pg.4}



Picket Frame {Pg.5}, Picket Wall {Pg.5}






Picket Frame {Pg.5}

Picket

Picket Frame {Pg.5}





Picket




Picket Wall {Pg.5}, Picket Field Tile {Pg.4}, Pencil {Pg.4}, Picket Start {Pg.4}

Cuenta con multitud de posibilidades de colocación
Gives us a wide range of collocations

Ejemplos de colocación /Tile layout patterns

- Picket Field Tile
- Picket Wall
- Picket Frame
- Picket piezas especiales / special pieces



Pasta Blanca / White Body



Brillo / Gloss






Relieve en la pieza/ Relief in piece



Revestimiento / Wall tiles



Lista de Packing / Packing list

Modelo Item	Referencia Reference	Lista de packing / Packing list						
		Piezas /m² Pieces/m²	Piezas /caja Pieces/box	m² / caja m² / box	caja/pallet box/pallet	m² / pallet m² / pallet	peso pallet (kg) pallet weight (kg)	Grupo Group
	Picket Wall (Quartz, Beryl, Moonstone, Hematite)	69,28	20	0,29	128	36,95	575	G11
	Picket Frame (Quartz, Beryl, Moonstone, Hematite)	69,28	16	0,23	128	29,56	590	G11
	Picket Field Tile (Quartz, Beryl, Moonstone, Hematite)	58	16	0,28	128	35,31	660	G6
	Picket Pencil (Quartz, Beryl, Moonstone, Hematite)	-	90	-	112	-	-	P1
	Picket Quartino (Quartz, Beryl, Moonstone, Hematite)	-	60	-	112	-	-	P1
	Picket Frame Start (Quartz, Beryl, Moonstone, Hematite)	-	40	-	-	-	-	P2
	Picket Start (Quartz, Beryl, Moonstone, Hematite)	-	40	-	-	-	-	P2

Características técnicas de la base / Technical characteristics of the wall						
Especificaciones técnicas Technical specifications		Norma Iso standard	Resultados Results		Requisitos / Requirements ISO 13006: 2012 Anexo/Annex L EN 14411: 2016 Anexo/Annex L	
	Características Dimensionales Dimensions	ISO 10545-2	Varios / Various		N≥15cm	
			Longitud / Length	Anchura / Width		
	Sobre la medida de fabricación From work size		0,00%, 0,0mm / 0,12%, 0,3mm	-0,12%, -0,1mm / 0,37%, 0,3mm	±0,5% / ±2,0mm	
	Rectitud de los lados Straightness of the sides		-0,04%, -0,1mm / 0,04%, 0,1mm	0,00%, 0,0mm / 0,00%, 0,0mm	±0,3% / ±1,5mm	
	Ortogonalidad Rectangularity		-0,16%, -0,4mm / 0,16%, 0,4mm	-0,12%, -0,1mm / 0,12%, 0,1mm	±0,5% / ±2,0mm	
	Curvatura lateral Edge curvature		-0,20%, -0,5mm / 0,00%, 0,0mm	0,00%, 0,0mm / 0,00%, 0,0mm	-0,3/+0,5 % / -1,5/+2,0mm	
	Curvatura central Centre curvature		-0,19%, -0,5mm / 0,00%, 0,0mm		-0,3/+0,5 % / -1,5/+2,0mm	
	Del alabeo From warpage		-0,04%, -0,1mm / 0,04%, 0,1mm		±0,5% / ±2,0mm	
	Grosor Thickness		0,00%, 0,0mm / 1,25%, 0,1mm		±10% / ±0,5mm	
	Absorción de agua Water absorption	ISO 10545-3	E=18,0% mín 17,3%		E>10% mín 9%	
	Resistencia a la flexión Modulus of rupture	ISO 10545-4	e ≥ 7,5mm		e ≥ 7,5mm	e < 7,5mm
	Fuerza de rotura Breaking strength		860N		≥600N	≥200N
	Resistencia a la flexión Modulus of rupture		Media=21 N/mm² Min=19 N/mm²		Media ≥ 12 N/mm²	Media ≥ 15 N/mm²
	Resistencia al choque térmico Resistance to thermal shock	ISO 10545-9	Resistente / Resistant		Valor declarado / Declared value	
	Coefficiente térmico de dilatación lineal Thermal coefficient of linear expansion	ISO 10545-8	5,9 x 10 ⁻⁶ °K ⁻¹		Valor declarado / Declared value	
	Resistencia al cuarteo Crazing resistance	ISO 10545-11	Resistente / Resistant		Exigido / Required	
	Resistencia química Chemical resistance	ISO 10545-13				
	Productos domésticos y aditivos piscinas Household chemicals and swimming pool salts		GA		Mín GB	
	Ácidos y bases baja concentración Low concentration of acids and alkalis		GLA		Valor declarado / Declared value	
	Resistencia al manchado Stain resistance	ISO 10545-14	5		Mín 3	
	Calidad de la superficie Surface quality	ISO 10545-2	100%		≥95%	

HRG

HERALGI

📍 Camí del palmeral s/n 12200 Onda (Castellón)

✉ info@heralgi.com