





TECHNICAL SPECS		
Region	North America	Europe and UK
Voltage	220V Single Phase	380-415V 3 Phase
Plug	30A single phase NEMA L6-30P	32A 5 Pin 3 Phase
Power Frequency	50/60Hz	50Hz
Power Output	5HP (3.7kW)	5.5kW
Motor Speed	0 - 1800rpm	
<b>Grinding Head Speed</b>	0 - 1500rpm	
Planetary Plate Speed	0 - 540rpm	
Display	LED Digital RPM	
Drive	Steel Gear	
Grinding Width	21.7" (550mm)	
Head Diameter	9" (230mm)	
<b>Grinding Heads</b>	3	
Water Tank	7.9 gal (30L)	
Vacuum Port	2" (50mm)	
Length	38.2" (970mm)	
Width	21.7" (550mm)	
Height	33.5" (850mm)	
Weight	369 lbs (180kg)	

## INNOVATECH'S HIGH PRODUCTIVITY 3-HEADED, GEAR DRIVEN, PLANETARY GRINDER

Innovatech's Predator Concrete Grinders are manufactured with some of the highest standards in the industry, making them extremely reliable, productive, balanced and easy to use for any operator.



- · Precision balanced 3-head planetary design
- · Exceptional balance
- · Heavy-duty steel frame
- · Easy height adjustment handle
- · Assortment of tooling available
- Easy on-site maintenance or repair with standard tools
- · Variable speed control
- · Forward/reverse grinding
- · Integrated water tank
- · Bright LED work light included
- · Slide Mag or 3 hole tooling plates
- · Additional weight included (77lbs 35kg)



