



Angle Fit™ Rubber Stair Treads with Integrated Riser

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Rubber Stair Treads A.D.A., Visually-Impaired, and California Title 24 Compliant

1.1. **Manufacturer:**

Tarkett Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarketta.com

1.2. Proprietary Product Description:

1.1.1. **Construction:** Tarkett Rubber Stair Treads are manufactured from a homogeneous composition of 100% synthetic rubber, high quality additives, and colorants to meet the performance requirements of ASTM F-2169 Standard Specification for Resilient Stair Treads, Type TS, Class 1 and 2, Group 1 and 2. All Tarkett Stair Treads are available with a 2" (5.08 cm) wide strip of contrasting color to comply with A.D.A., Visually-Impaired, and California Title 24 requirements. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements.

1.2.1. Styles & Physical Characteristics:

Round Raised Disk Pattern Rubber Stair Tread with Integrated Riser (**RNRDTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VIRNRDTR with 2" (5.0 cm) wide contrasting color grit tape insert
VIRNRDTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Square Raised Disk Pattern Rubber Stair Treads with Integrated Riser (**RNSQTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VIRNSQTR with 2" (5.0 cm) wide contrasting color grit tape insert
VIRNSQTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Hammered Surface Texture Rubber Stair Tread with Integrated Riser (**HNTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VIHNTR with 2" (5.0 cm) wide contrasting color grit tape insert.
VIHNTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Bamboo Surface Texture Rubber Stair Tread with Integrated Riser (**BMNTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VIBMNTR with 2" (5.0 cm) wide contrasting color grit tape insert
VIBMNTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Cubis Surface Texture Rubber Stair Tread with Integrated Riser (**CUBTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VICUBTR with 2" (5.0 cm) wide contrasting color grit tape insert.
VICUBTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Fast Lane Surface Texture Rubber Stair Tread with Integrated Riser (**CFLNTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VICFLNTR with 2" (5.0 cm) wide contrasting color grit tape insert.
VICFLNTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Diamond Texture Rubber Stair Treads with Integrated Riser (**CNNTR**), 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VICNNTR with 2" (5.0 cm) wide contrasting color grit tape insert.
VICNNTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip

Rice Paper Texture Rubber Stair Tread (**FRPANTR**), Integrated Riser, 19" (48.3 cm) overall width, 2" (5.08 cm) hinged square nose configuration.

For visually impaired specify:

VIFRPANTR with 2" (5.0 cm) wide contrasting color grit tape insert.
VIFRPANTRS with 2" (5.0 cm) wide contrasting solid rubber color insert strip



Angle Fit™ Rubber Stair Treads with Integrated Riser

Product Specification

1.1.2. Sizes:

Raised Round, Raised Square and Hammered rubber stair treads available in 3', 3-1/2', 4', 4-1/2', 5', and 6' (.91 m, 1.07 m, 1.22 m, 1.37 m, 1.52 m, and 1.83 m), 7 ft. (2.13 m), 8 ft. (2.44 m), and 9 ft. (2.74 m) lengths]

Bamboo, Cubis, Fast Lane, Diamond, and Rice Paper rubber stair treads available in 3', 3-1/2', 4', 4-1/2', 5', and 6' (.91 m, 1.07 m, 1.22 m, 1.37 m, 1.52 m, and 1.83 m)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 2.2. **Abrasion Resistance** (ASTM D 3389): < 1 gram weight loss
- 2.3. **Slip Resistance** (ASTM D 2047): Meets and exceeds a static coefficient of friction of 0.8
- 2.4. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux): Class 1 (Minimum 0.45 W/cm²)
- 2.5. **Smoke Development** (ASTM E 662/NFPA 258): less than 450
- 2.6. **Canadian Flammability & Smoke** (CAN/ULC S102.2):
≤ 300 Flame Spread & ≤ 500 Smoke Developed

3. INSTALLATION

- 3.1. See Tarkett Stair Tread installation instructions for complete details.
- 3.2. **Adhesives:**
 - **Tarkett 965 Adhesive Coverage:**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous Substrate: 150-175 sq. ft. per gallon
 - **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)
Application: Brush or roller
Approximate coverage:
1 kg Unit (0.95 Qt) – 24 to 36 sq. ft.
6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft.

- **Tarkett 930 Two-Part Epoxy Caulking Compound**

Application: 30 oz. cartridge (Use Tarkett 530 dual-cartridge dispenser gun with cartridge)

Coverage: Approximately 50 linear ft. / cartridge

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Rubber Stair Treads Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com