



1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Homogeneous sheet floor coverings, non-directional patterned, designed for durability and commercial interiors.
- 1.2. Recommended areas for use:
 - Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories
 - Education – Classrooms, corridors, multipurpose rooms, gymnasiums, laboratories, cafeterias
 - Offices – Break rooms, offices, corridors, cafeterias, lavatories
 - Retail – Sales areas, offices
 - Hospitality – Corridors, vending areas, lobbies, bathrooms
- 1.3. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com
- 1.4. **Proprietary Product Description:**
- 1.4.1. **Construction:** Tarkett's iQ Homogeneous flooring are composed of a 0.080" (2 mm) thick unique construction that is abrasion resistant and requires no wax. No need for polish or wax throughout the life of the product. Construction allows for dry buff for ease of maintenance.
- 1.4.2. **Styles:**
 - Rolls
 - Tiles
- 1.4.3. **Sizes / Packaging:**
 - **Rolls** available in 6.5' (2 m) wide by 75.5' (23 m) long, & approximately 6.98 lbs/yd² (3.16 kg/m²)
 - **Tiles** sizes/Packaging:
24" x 24" (61 cm x 61 cm), 14 pc/carton, 56 ft² (5.21 m²), & 43 lbs/carton (19.5 kg)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets performance standards of ASTM F1913, Standard Specification for Vinyl Sheet Floor Covering without Backing and ASTM F1700 Standard Specification for Solid Vinyl Tile.
- 2.2. **Polyurethane Reinforced** (ASTM F410): Yes
- 2.3. **Tile Squareness** (ASTM F2055): Passes
- 2.4. **Tile Dimensional Stability** (ASTM F2199): Passes
- 2.5. **Flexibility** (ASTM F137): Passes
- 2.6. **Total Thickness** (ASTM F386): 0.080 in. (2 mm)
- 2.7. **Static Load Limit** (ASTM F970): 500 psi, $\leq 0.005"$
- 2.8. **Resistance to Heat** (ASTM F1514): $\Delta E \leq 8$

- 2.9. **Resistance to Light** (ASTM F1515): $\Delta E \leq 8$
- 2.10. **Slip Resistance** (ASTM D2047): SCOF ≥ 0.5
- 2.11. **Fire Performance** (ASTM E648 Flooring Radiant Panel): Class 1

3. INSTALLATION

- 3.1. See homogeneous sheet or tile flooring installation instructions for complete details.
- 3.2. **Sheet Adhesive:**
 - **Tarkett 925 Adhesive Coverage:**
Porous Substrate: 250-300 sq. ft./gal.
Non-porous Substrate: 250-300 sq. ft. per gallon
 - **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
 - **Tarkett RollSmart Adhesive Coverage:**
Approximate Coverage:
Porous & Non-porous Substrate: 350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)
 - **Tarkett Cold Weld Liquid Coverage:** 175 – 200 lin. ft. per 4.5 oz. tube
- 3.3. **Tile Adhesive:**
 - **Tarkett 926 Adhesive Coverage:**
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
 - **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to iQ Flooring Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 20 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com