

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	7" x 48"
Bevel	Painted/Beveled
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	15-Year
Commercial Warranty	10-year

**The Andover™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	4.4MM
Core thickness	3.4MM
XPE Backing	1.0MM
Wear Layer	6 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	25-Year

**The Ashton Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	4.4MM
Core thickness	3.4MM
XPE Backing	1.0MM
Wear Layer	6 mil
Plank size	9" x 60"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	25-Year

**The XL Ashton Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	N/A

**The Cyrus™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	9" x 60"
Bevel	Painted/Beveled
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	N/A

**The XL Cyrus™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	2MM
Wear Layer	12 mil
Plank size	6" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 51 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Certifications	FloorScore & Greenguard
Residential Warranty	25-Year
Light Commercial Warranty	6-Year
Commercial Warranty	N/A

**The Glenridge™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	2MM
Wear Layer	6 mil
Plank size	6" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 51 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Good
Certifications	FloorScore & Greenguard
Residential Warranty	15-Year
Light Commercial Warranty	N/A
Commercial Warranty	N/A

**The Katavia™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	9" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	15-Year
Commercial Warranty	10-Year

**The Laurel Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.



## Specification Sheet

Total thickness	8MM
Core thickness	6MM
XPE Backing	2MM
Wear Layer	22 mil
Plank size	9" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	25-Year
Commercial Warranty	20-Year

**The Laurel Reserve Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	6.5MM
Core thickness	5.5MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime (with dent warranty*)
Light Commercial Warranty	20-Year
Commercial Warranty	15-year

**The Prescott™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	6.5MM
Core thickness	5.5MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	9" x 60"
Bevel	Painted/Beveled
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	20-Year
Commercial Warranty	15-Year

**The XL Prescott Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	2.5MM
Wear Layer	20 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 53 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	15-Year
Commercial Warranty	10-Year

**The Wilmont™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	12" x24"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
DCOF	>0.42
ANSI A137.1	Pass
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	N/A

**The Trecento™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msisurfaces.com/Everlife](http://www.msisurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.

## Specification Sheet

Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	18" x 36"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	$\Delta$ IIC $\geq$ 26 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	$\geq$ 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Patented Locking System (Angle / Angle)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	N/A

**The XL Trecento Collection by MSI contains no phthalates and uses 100% virgin vinyl.**

**Disclaimer:**

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to [www.msissurfaces.com/Everlife](http://www.msissurfaces.com/Everlife) or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.