

# ARDEX PANDOMO® W1

## Wall Design Decorative Finishing Compound

### Key Features

- Trowelable
- Portland cement-based
- Use over drywall or masonry
- Use for walls and ceilings
- Excellent non-sag properties
- Color with  
ARDEX PANDOMO® CC Color Concentrates

### Installation

- **General priming recommendations:**
  - ARDEX P 51™ PRIMER diluted 1:3 with water
- **Packaging:** 11 lbs. (5 kg)
- **Coverage:** 25 to 35 ft<sup>2</sup> per bag at 1/8"  
(2.3 to 3.25 m<sup>2</sup> at 3 mm) (2 coats)
- **Thickness:**
  - Install from 1/16 to 1/2" (2 to 12 mm) for each coat
- **Working Time:** 30 minutes
- **Time to Second Coat:** 1 hour
- **Begin Processing:** 5 hours
- **Seal with ARDEX PANDOMO® SL Stone Oil**

### Performance

- **ASTM C109 mod (air cure only) Compressive Strength:** 1900 psi (133 kg/cm<sup>2</sup>) at 28 days
- **ASTM C348 Flexural Strength:**  
725 psi (50 kg/cm<sup>2</sup>) at 28 days



PANDOMO®

AF398 06/15

For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google play.



Refer to the technical data sheet at [www.ardexamericas.com](http://www.ardexamericas.com) or call 888-512-7339 prior to installation. For free ARDEX product training, click on ARDEX Academy.

© 2014 ARDEX Engineered Cements, L.P. All rights reserved.



AMERICAS

888-512-7339

+1-724-203-5000

[www.ardexamericas.com](http://www.ardexamericas.com)