

ARDEX PANDOMO® ES/PS

Clear Waterborne Epoxy Floor Primer

Clear Waterborne Two-Part Urethane Protective Wear Layer

ARDEX PANDOMO® ES

Waterborne, two-part epoxy base coat primer. Use as a system with ARDEX PANDOMO® PS Urethane Protective Wear Layer to seal and protect.

Key Features

- Designed for ARDEX PANDOMO® CF1, CF3, and K2
- Interior use

Installation

- **Packaging:** 1 gallon (Part A: 0.80 gal; Part B: 0.20 gal) (Part A: 3 L Part B .75L)
- **Coverage:** 250 to 300 ft² (23 to 28 m²) per unit
- **Installation:**
 - 5 to 7 mils wet, which yields 2 to 3.5 mils dry (127 to 178 / 50 to 90 microns)
- **Pot Life:** 2 hours
- **Dry Time:** 2 to 4 hours to touch
- **Apply ARDEX PANDOMO® PS:** 4 to 6 hours

Performance

- **Solids content:** 43% (+/- 2%) by weight
- **Adhesion:** > 425 psi (concrete failure, no delamination)
- **VOC:** 145 g/L

ARDEX PANDOMO® PS

A two-part urethane protective wear layer designed to be used as a top coat over ARDEX ES Epoxy Floor Primer.

Key Features

- Designed for ARDEX PANDOMO® CF1, CF3, and K2
- Satin finish, non-darkening
- Stain resistant
- UV-stable
- Interior use only

Installation

- **Packaging:** One 5L (16.9 fl. oz.) bottle of Part A (Base)
Two 500mL (16.9 fl. oz.) bottles of Part B (Cross Linker)
- **Coverage:** 1000 to 1050 ft² (93 to 97.5 m²) per kit
- **Pot Life:** 1 hour
- **Time to Re-coat:** 2 hours
- **Light Foot Traffic:** 24 hours
- **Full Cure:** 7 days

Performance

- **VOC:** < 110 g/L
- **Gloss Level:** Approx. 28

ARDEX®
PANDOMO