



HYDRO BAN® Nail Circles - Peel & Stick

DS-65487-1125

**Globally Proven
Construction Solutions**



- Pliable – conforms easily to substrate
- Complete line of accessories – single source supply
- Compatible with HYDRO BAN products++
- † Refer to requirements for specific substrate to which the HYDRO BAN® Sheet Membrane will be bonded

Suitable Substrates (Interior Use Only)

- Concrete
- Concrete Masonry
- Brick Masonry
- Cement Mortar Bed
- Cement Plaster
- Gypsum Wallboard
- Exterior Glue Plywood (Interior Only)
- Ceramic Tile and Stone
- Cement Terrazzo
- Cement Backer Board
- Poured Gypsum Underlayment

Packaging

2" Diameter / 200 per roll / 1 Roll per box

Approximate Coverage

HYDRO BAN® Peel & Stick Nail Circles	
2"	200 per roll 1 roll per box

Limitations

- DO NOT bond to particle board, luan, OSB, interior glue plywood, Masonite® or hardwood surfaces.
- Do not use as a primary roofing membrane over occupied space. For more information on installation of tile over wood decks, or, over occupied or finished spaces please refer to TDS 157 "Exterior Installation of Tile and Stone Over Occupied Space."
- Do not use over dynamic expansion joints, structural cracks or cracks with vertical differential movement.
- HYDRO BAN® Sheet Membrane is not recommended for submerged applications. For these applications, use HYDRO BAN waterproofing membrane.
- Do not use over existing cracks.

1. PRODUCT NAME

HYDRO BAN® Nail Circles - Peel & Stick

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

The peel-and-stick versions feature a non-organic adhesive backing to speed installation and reduce the risk of mold or mildew growth. Offered in multiple widths and thicknesses, these flexible tapes conform to surfaces and overlaps to protect against moisture intrusion in showers, steam rooms, and tiled wet areas.

Uses

- Interior applications
- Showers or tub surrounds
- Steam rooms and steam showers
- Bathrooms
- Commercial and residential kitchens
- Backsplashes
- Walls and floors
- Wet areas

Advantages

- ANSI A118.10 - Exceeds all requirements

- Do not expose to negative hydrostatic pressure, rubber solvents or ketones.
- Must be covered with ceramic tile, stone, brick, screeds, terrazzo, or other traffic-bearing finish. Use protection board for temporary cover.
- Do not install directly over single layer wood floors, plywood tubs/showers/fountains or similar constructs.
- Not for use beneath cement or other plaster finishes. Consult with plaster manufacturer for their recommendations when waterproofing membrane is required under plaster finishes.
- Not for use under self-leveling underlayments or decorative wear surfaces.
- Note: Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/480 for thin bed stone installations where L=span length.
- Consult gypsum board manufacturer and local building code for use in wet areas

Cautions

- Protect finished work from traffic until fully cured.
- For white and light-colored marbles, use a white LATICRETE® Latex Portland Cement Thin Set Mortar.
- Use care not to damage HYDRO BAN Sheet Membrane prior to installation of tile or stone finishes. Cover with protection board to protect from foot traffic and other trades when installing on horizontal surfaces

4. TECHNICAL DATA

Applicable Standard

- Meets or exceeds ANSI A118.10 specifications

Physical Properties

Working Properties

HYDRO BAN Peel & Stick Sheet Membrane products are constructed of two outer layers of non-woven polypropylene and one inner layer of polyethylene. This three layer membrane when properly installed will protect tile installations from moisture migration and minor substrate cracking.

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

• Surface Preparation

Surface temperature must be 50 – 90°F (10 – 32°C) during application and for 24 hours after installation. All substrates must be structurally sound, clean and free of dirt, oil, grease, paint, laitance, efflorescence, concrete sealers or curing compounds. Make rough or uneven concrete smooth to a wood float or better finish with a suitable LATICRETE underlayment. Do not level with gypsum or asphalt based products. Maximum deviation in plane must not exceed 1/4" in 10 ft (6 mm in 3 m) with no more than 1/16" in 1 ft (1.5 mm in 0.3 m) variation between high spots. Dampen hot, dry surfaces and sweep off excess water—installation may be made on a damp surface.

1. Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Installer must verify that deflection under all live, dead and impact loads of interior plywood floors does not exceed industry standards of L/360 for ceramic tile and brick or L/480 for stone installations and L/600 for all exterior veneer applications where L=span length.
2. Minimum construction for interior plywood floors.

• Treat Cracks & Joints

Fill all substrate cracks, cold joints, and control joints to a smooth finish using a LATICRETE® polymer fortified thin-set.

Application

- Clean Surface of dust, dirt and debris.
- Identify number of nail circles required for project
- Remove HYDRO BAN® Peel & Stick Nail Circle from roll.
- Placing one edge of the tacky membrane on the designated surface.
- Firmly press circle onto the surface using flat edge of trowel or grout float from one edge of the membrane to the other, removing air bubbles.

Control Joints

Ceramic tile, stone and brick installations must include sealant filled joints between the ceramic tile, stone or brick which is over any control joints in the substrate. However, the sealant filled joints can be offset horizontally by as much as one tile width from the substrate control joint location to coincide with the grout joint pattern.

Movement Joints

Ceramic tile, stone and thin brick installations must include expansion joints at coves, corners, other changes in substrate plane and over any expansion joints in the substrate. Expansion joints in ceramic tile, stone or brickwork are also required at perimeters, at restraining surfaces, at penetrations and at the intervals described in the Tile Council of North America, Inc. (TCNA) Handbook Installation Method EJ171. Use LATASIL™ and backer rod.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 1 Year Product Warranty (US) (English)
- 10 Year System Warranty (US) (English)
- 25 Year System Warranty (US) (English)
- Lifetime System Warranty (US) (English)

8. MAINTENANCE

Non-finish LATICRETE and LATAPOXY installation materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE

Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 230.10: LATICRETE 10 Year System Warranty
- DS 025.0: LATICRETE 25 Year System Warranty
- DS 230.99: LATICRETE Lifetime System Warranty
- DS 677.0: 254 Platinum
- DS 663.0: HYDRO BAN
- DS 6200.1: LATASIL
- DS 035.0: HYDRO BAN Bonding Flange Drain
- DS 034.0: HYDRO BAN Linear Drain
- TDS 157: Exterior Installation of Tile and Stone Over Occupied Space

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2025 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.