



UltraCare™

Cement Grout Haze Remover



DESCRIPTION

UltraCare Cement Grout Haze Remover is a professional-strength formulation that helps to remove cement grout haze from tile, concrete and stone surfaces. It is an acidic, low-odor, non-flammable, easy-to-use, water-based formula.

FEATURES AND BENEFITS

- Professional-strength formula
- Removes cement grout haze
- Easy-to-use, water-based formula

WHERE TO USE

Most acid-resistant natural stone surfaces including slate, granite, ceramic and porcelain tiles, as well as quarry tile, brick and sealed Saltillo

LIMITATIONS

- Ensure that the product does not come in contact with any non-recommended surface. It will etch polished marble and limestone, and may lighten the color of cementitious materials.
- Do not mix with other chemicals.
- Do not apply product with a sprayer.

Consult MAPEI's Technical Services Department for application recommendations regarding surfaces and conditions not listed.

INDUSTRY STANDARDS AND APPROVALS

- Meets all EPA and SCAQMD standards for VOCs

SURFACE PREPARATION

- Be sure all surfaces to be treated are swept or vacuumed to remove loose debris.
- For best results, pre-wet the surface with water.

INSTRUCTIONS

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

Always test first in several inconspicuous areas to confirm desired results.

1. Avoid skin and eye contact by wearing chemical-resistant gloves and protective lenses.
2. Shake well before using. Do not dilute before applying.
3. Working in a small, manageable area of 15 sq. ft. (1.39 m²), liberally apply an even coat over the required area with a paint brush, mop or paint pad. Do not apply with a sprayer.
4. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
5. Allow product to stand on the surface for 10 to 15 minutes.
6. Do not let *UltraCare* Cement Grout Haze Remover dry on the surface. Keep the surface wet by adding more product.
7. Agitate surface with a soft brush or white scrub pad after testing a small area first to make sure that brush or pad will not scratch the surface.
8. Wipe up residual cleaner with clean, dry cloths.
9. Rinse the surface well with clean water and allow to thoroughly dry.
10. If more than one application is required, repeat steps 3 through 9.



Product Performance Properties

Laboratory Tests	Results
VOCs (Rule #1168 of California's SCAQMD)	0 g per L

Shelf Life and Application Properties

Shelf life	Up to 5 years when stored in original, unopened packaging at 73°F (23°C)
Appearance	Clear
Odor	Slight odor
Physical state	Liquid

Packaging

Size
Bottle: 1 U.S. qt. (946 mL)

Approximate Product Coverage*

Size	Coverage
1 U.S. qt. (946 mL)	20 to 50 sq. ft. (1.86 to 4.65 m ²)

* Coverage will vary depending on density, porosity, texture, surface absorption, time that solution is left on surface, application method and severity of the problem.

Close container tightly after each use. Store in original container only. Store between the temperatures of 35°F to 90°F (2°C to 32°C). Do not allow to freeze.

For ongoing maintenance instructions, see the "UltraCare Maintenance Guide" in the Reference & Installation Guides category of the Related Documents section of the Tile & Stone Installation Systems page on MAPEI's Website.

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI meets the health and well-being requirements of product certification programs, contact the MAPEI Sustainability Team at 1-800-992-6273.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at

www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:



MAPEI Headquarters of North America
1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) /
(954) 246-8888

Technical Services
1-800-992-6273 (U.S. and Puerto Rico)
1-800-361-9309 (Canada)
Customer Service
1-800-42-MAPEI (1-800-426-2734)

Services in Mexico
0-1-800-MX-MAPEI (0-1-800-696-2734)
Edition Date: June 5, 2019
MK 3000077 (19-1541)

For the most current BEST-BACKED™ product data and warranty information, visit www.mapei.com.

All Rights Reserved. © 2019 MAPEI Corporation.