



Walk
with
confidence.

Product Information

Plasticove - Flexible

| | |
|---------------------------------|---|
| Product Code: | 9300 |
| Product Family: | CORE Vinyl Coving |
| Manufacturer: | GRIP-RITE CARPET ACCESSORIES LTD. 12002 75 ST NW EDMONTON, AB T5B 2B6 |
| Contact Info: | Toll-Free Ph: 800-732-8289 Web: coreflooring.ca |
| Origin: | Made in Canada with some imported components. |
| Section: | 09 65 00 Resilient Flooring |
| Related Section: | 09 68 00 Carpeting |
| Usage: | Medium cove in a flexible format for curved walls. |
| Physical Char: | Solid Flexible Thermoplastic Vinyl |
| Dimensions: | Refer to Profile for dimensions |
| Packaging: | 20 Pieces per 3.03" x 149" Tube |
| Colour Selection: | Variable - recycled material. |
| DSH: | Store in original packaging until required for use. |
| Conditions: | Substrate must be clean and dry and at normal operating temperature. Use appropriate Installation Guide for directions. |
| Warranty: | Limited 1 Year Warranty. See below for details. |
| 2-2-A Material: | Thermoplastic Vinyl |
| 2-2-B Physical Prop: | Solid, Flexible, Resilient. |
| 2-2-B-1 Recy Cont: | 100% Pre-consumer recycled content. |
| 2-2-B-2 Density: | 1.38 g/cm ³ |
| 2-2-B-3 Hardness: | 75 Shore A |
| 2-2-B-6 Flame Spr Ind: | ASTM E 84, Class B |
| 2-2-B-7 MRM: | Resistant. |
| 2-2-B-8 Flexibility: | Will not crack, break, or show signs of fatigue under normal use. |
| 2-2-B-9 Direct Grade: | Allowed. |
| 2-2-B-10 Direct Masonry: | Allowed. |

| | |
|--------------------------------------|--|
| 2-2-B-11 Thermodynamic: | Not meant to be stretched. |
| 2-2-B-12 Heat Forming: | Not Recommended. |
| 2-2-B-13 Loading: | Not load-bearing. |
| 2-2-B-14 Paintability: | N/A |
| 2-2-B-15 Colourfastness: | N/A (underfloor use) |
| 2-2-B-16 Environmental: | N/A |
| 2-2-B-17 Flash Point: | |
| 2-2-B-18 Ignition Conditions: | Will burn in a fire. |
| 2-2-B-19 Extinction: | Use appropriate means for surrounding materials. |
| 2-2-B-20 Reactivity: | Chemically Stable. |

INSTALLATION INSTRUCTIONS

CORE Vinyl Coving

| | |
|-------------------------------------|--|
| <i>Introduction:</i> | CORE Vinyl Coving is designed to provide a sturdy underflooring support to carpet and sheet floor coving. |
| <i>Handling and Storage:</i> | Store in original packaging until needed for installation. Site-condition CORE Vinyl Coving to room temperature (18°C to 24°C) for 24 hours in order to achieve proper bonding of adhesives. |
| <i>Subfloor Preparation:</i> | 1. All subfloors and wall surfaces must be clean, smooth, and dry. Dust, scale, and loose particles must be removed. The surface must be free of solvents, paint, grease, oil, wax, alkali, sealing/curing compounds, and any other foreign material, which could affect adhesive bonding. |
| <i>Product Preparation:</i> | If product has been coiled or twisted, lay flat and allow to relax for 24 hours before installing. |
| <i>Installation:</i> | <p>Areas to receive coving, as well as coving itself, should be preconditioned to at least 18°C for 24 hours before, during, and after installation.</p> <p>For interior installation only; note that warranty does not apply for outside installations.</p> <p>Dry-fit the coving first in order to determine fit; trim to size with a utility knife or carpet shears.</p> <p>Install using a construction-grade Contact Cement, using manufacturer's instructions regarding usage.</p> <p>If questions arise that have not been addressed in this document, contact your local CORE Flooring Accessories distributor for assistance or CORE Flooring Customer Service at 1-800-732-8289.</p> |

Maintenance Guide

CORE Vinyl Coving

| | |
|------------------------------------|---|
| <i>Regular Maintenance:</i> | This is an under-floor product and normally requires no maintenance after being properly installed. |
|------------------------------------|---|

Special Instructions:

Warranty

CORE Vinyl

Warranty Details:

CORE FLOORING ACCESSORIES LIMITED WARRANTY - VINYL PRODUCTS

For a period of one (1) year from the date of shipment, Grip-Rite Carpet Accessories Ltd. (Grip-Rite) makes the following warranty, subject to the terms and conditions specified herein, for all CORE Flooring Accessories™ (CORE) thermoplastic vinyl products.

CORE products will conform to the Specifications description, with only such reasonable variations as is acceptable in the trade; it is fit for the ordinary purposes for which the product is used; and it will be adequately packaged and labeled.

Grip-Rite will replace any defective product at no charge if the defect is found prior to installation. If the customer believes the product to be defective after installation, the customer must promptly notify Grip-Rite and permit an inspection of the product. If, upon inspection, Grip-Rite determines the product to be defective, subject to the limitations contained in this warranty, Grip-Rite will replace the defective product at its cost in the affected room or area.

To be eligible for replacement under any of these warranties, the customer must give Grip-Rite written notice of any claimed defect immediately upon learning of the defect and in no event more than 90 days after the claimed defect is discovered. Notice shall be given to Grip-Rite at its Corporate Address of 12002 – 75th Street, Edmonton, Alberta T5B 2B6.

Excluded from Warranty:

These warranties do not apply to the following:

1. The exact matching of shade, colour, or embossing.
2. Any express or implied promise made by any salesman or representative that exceeds the limits of these warranties.
3. Tears, burns, cuts, or other damage due to improper handling, installation, improper use of cleaning agents, or of improper maintenance methods.
4. Labor costs for installation of original or replacement material.
5. Sale of "Seconds", "Off Goods" or other irregular (non-first-quality) flooring materials. With respect to "Seconds" or "Off Goods", such are sold "as is", and Grip-Rite makes no warranties whatsoever, express or implied with respect thereto, including warranties of merchantability or fitness for a particular purpose.
6. Problems caused by moisture, hydrostatic pressure, or alkali in the sub-floor.
7. Problems caused by use, handling, maintenance, or installation that is contrary to Grip-Rite's specifications, recommendations, or instructions.
8. Material installed with obvious defects.
9. Damage to flooring products from high heels, spike heels, pallet jacks, construction carts, motorized traffic, or the moving of furniture.
10. Installation of Grip-Rite products with adhesives other than those recommended by Grip-Rite.
11. Exterior installations. Grip-Rite's products are designed for interior applications only.

12. Fading and/or discoloration resulting from heavy sunlight penetration and ultraviolet ray exposure from direct or glass-filtered sunlight.
13. Material that is not installed and maintained as recommended by Grip-Rite.
14. Damage to flooring products from pallet jacks, construction carts, motorized traffic, or the moving of furniture.
15. Premature wear and deterioration from furniture, spikes, or skate blade exposure.
16. Differences in colour between products and printed or electronic images.
17. Embossing deviations between product and samples, photography, and printed colour illustrations.