



Size
9" x 60" *nominal* (23 cm x 152.5 cm)
6 mm thick

Wear Layer
20 mil / UV-Cured Urethane

Edge Treatment
Four-Sided Color-Enhanced Bevel

Installation
Angle-Angle Click Floating Floor
(on, above or below grade)

Attached Cushion
For superior sound abatement
and easier installation.

Coordinating Moldings
See nextfloor.net for more details

Packaging
6 pieces per carton (40 lbs)
22.5 SF per carton
52 cartons per pallet
21 pallets per container

Testing
Critical Radiant Flux
Surface Flammability
Coefficient of Friction
Sound Transmission Class (STC)
Impact Insulation Class (IIC)
High Frequency Impact Insulation Class(HIIC)
Static Load Limit
Floor Score Certified
Phthalate Free
100% Virgin PVC

Warranties
Lifetime Waterproof
Lifetime Residential Wear
Lifetime No Cupping*
30-Year Commercial Wear†

*When properly installed; see full warranty text at nextfloor.net

†For moderate traffic areas without rolling loads, heavy fixtures or ramps.

| | |
|-------------|-------------------------------------|
| ASTM E648 | Class I |
| DOC FF 1-70 | Passed |
| ASTM 2047 | Passes > 0.6 |
| ASTM E64 | 65 |
| ASTM E73 | 72 |
| ASTM E89 | 92 |
| ASTM F970 | exceeds 3000 lbs without cushion |



Sample SKUs

Handle Boards
HB527NF-B
5 per carton (72 lbs)

Strap Sets
SS527NF-B
5 per carton (55 lbs)

Step Up Display
8CARDS527NF-1B
8CARDS527NF-2B
FIXT527NF
Packaged in 3 cartons (170 lbs)

Update Kit
2022UPDATE527
Packaged in 1 carton (55 lbs)

