



Size
 9" x 60" *nominal* (23 cm x 152.5 cm)
 5.7 mm thick

Wear Layer
 20 mil / UV-Cured Urethane

Edge Treatment
 Four-Sided Color-Enhanced Bevel

Installation
 Floating Floor, Fold-Down,
 Drop Lock System
(on, above or below grade)

Attached Cushion
 For superior sound abatement
 and easier installation.

Coordinating Moldings
 See nextfloor.net for more details

Packaging
 6 pieces per carton (40 lbs)
 22.5 SF per carton
 52 cartons per pallet
 21 pallets per container

Testing
 Critical Radiant Flux
 Surface Flammability
 Coefficient of Friction
 Static Load Limit
 Sound Transmission Class (STC)
 Impact Isulation Class (IIC)
 High Frequency Impact Isulation Class(HIIC)
 Floor Score Certified
 Phthalate Free
 100% Virgin PVC



Warranties
 Lifetime Waterproof
 Lifetime Residential Wear
 30-Year Commercial Wear
 See full warranty text at nextfloor.net

ASTM E648	Class I
DOC FF 1-70	Passed
ASTM 2047	Passes > 0.6
ASTM F970	exceeds 3000 lbs <i>without cushion</i>
ASTM E64	65
ASTM E73	72
ASTM E89	92

Sample SKUs

Handle Boards
 HB527NF-B
 5 per carton (72 lbs)

Strap Sets
 SS527NF-B
 5 per carton (55 lbs)

Step Up Display
 8CARDS527NF-1B
 8CARDS527NF-2B
 FIXT527NF
 Packaged in 3 cartons (170 lbs)

Update Kit
 2022UPDATE527
 Packaged in 1 carton (55 lbs)