

# Marvelous 425 Extra Heavy Commercial LVT



425 102  
Shoreline Oak



425 133  
Falcon Oak



425 101  
Cobblestone Oak



425 140  
Slate Oak



425 131  
Calm Oak



425 139  
Onyx Oak

**Size**  
7.25" x 48"  
3 mm thick

**Wear Layer**  
28 mil / UV-Cured Urethane  
MCX™ MicroCeramic Reinforced Resin

**Embossing**  
Realistic Texture  
Embossed in Register

**Edge Treatment**  
Beveled

**Installation**  
Full Spread Adhesive  
Recommended Adhesive:  
NEXT 1200™

**Packaging**  
14 pieces per carton (40 lbs)  
33.8 SF per carton  
55 cartons per pallet  
20 pallets per container

**Testing**  
Critical Radiant Flux  
Surface Flammability  
Coefficient of Friction  
Static Load Limit  
Sound Transmission Class (STC)  
Impact Isulation Class (IIC)  
High Frequency Impact Isulation Class(HIIC)  
Floor Score Certified  
Phthalate Free  
100% Virgin PVC



**Product Classification**  
ASTM F1700 Class III, Type B

**Warranties**  
Lifetime Waterproof  
Lifetime Residential Wear  
30-Year Commercial Wear  
*See full warranty text at nextfloor.net*

**Coordinating Moldings**  
*See nextfloor.net for more details.*

ASTM E648 Class I  
DOC FF 1-70 Passed  
ASTM 2047 Passed>0.6  
ASTM F970 1300 lbs  
ASTM E492 64  
ASTM E989 69  
ASTM E3222 89

**Sample SKUs**  
**Strap Sets**  
SS425NF  
*5 per carton (40 lbs)*