## 72025/72004/ 72005Q/72001Q





**Natural Cork Underlayment Sheets** 

For ceramic tile, stone, marble, glued wood flooring and floating floor systems

## **FEATURES & BENEFITS:**

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Use under ceramic tile, stone, marble, glued wood flooring and floating floor systems
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and looselay configurations\*

Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

| 2' x 3' Cork Underlayment Sheets      | R-Value** | Acoustical Performance                  | IIC | STC | FIIC |
|---------------------------------------|-----------|---|-----|-----|------|
| 72025 - 2.5 mm (1/8")                 |           |   |     |     |      |
| Quantity: 116 sheets/case             | 0.31      | With 8" cement slab                     |     |     | 34   |
| Coverage: 696 ft <sup>2</sup> /case   |           | With 6" cement slab & suspended ceiling | 60  | 59  |      |
| 72004 - 4 mm (3/16")                  |           |   |     |     |      |
| Quantity: 76 sheets/case              | 0.495     | With 8" cement slab (engineered wood)   |     |     | 34   |
| Coverage: 456 ft²/case                |           |   |     |     |      |
| 72005Q - 6 mm (1/4")                  |           |   |     |     |      |
| Quantity: 5 sheets/pack, 8 packs/case | 0.74      | With 6" cement slab                     | 51  | 52  | 22   |
| Coverage: 30 ft <sup>2</sup> /case    |           | With 6" cement slab & suspended ceiling | 61  | 60  |      |

## 72001Q - 12 mm (1/2")

Quantity: 25 sheets/case Coverage: 150 ft²/case

\* For a list of recommended adhesives to use for glue-down installations, please go to www.gep.com or call 800-840-9422.

## The Brand that Stands for Excellence.

www.QEP.com

U.S. Headquarters **866 435 8665** 

Canada **800 840 9422** 

Europe/Middle East **0031 24 6485348** 

Australia **011 61 3 9797 1888** 

New Zealand 64 9 415 9700

<sup>\*\*</sup> R-Value - Rating used to measure resistance to heat flow.