

NUEVA FLOOR SEALER

DEBUT ACRYLIC SEALER - UNDER COATER

DESCRIPTION

Nueva Floor Sealer is an acrylic water base sealer. It can be used on almost all types of floor surfaces. Ideally suited to protect high traffic areas.

MAIN USE

Nueva Floor Sealer, acrylic water emulsion sealer, sealer, is made to be used on all types of resilient surfaces such as vinyl, vinyl asbestos, rubber, asphalt linoleum tiles, etc... It can also be used on non-resilient hard surfaces such as terrazzo, ceramic, quarry tiles and concrete floors.

ADVANTAGES

Makes the finish look better longer. Any finish-applied levels more evenly, coats better with **Nueva Floor Sealer** as a base. Gives the floor a smoother surface appearance, more gloss, greater resistance to black marking and scuffs **Nueva Floor Sealer** has firm bonding and penetrating characteristics. Will not discolour. It adds depth of beauty every time. **Nueva Floor Sealer** makes a good-looking floor better, longer. **Nueva Floor Sealer** is easily and quickly removed with AGIVIT.

HOW TO USE

Keep in mind that the preparation of the floor is very important.

- First prepare a stripping solution of Floor Stripper (amount of mixed dilution will depend on the amount of accumulations of the floor finish)
- Spread solution on the floor.
- Use a floor machine with the recommended stripping pad.
- Strip the floor with a machine in a rotating motion.
- Pick up solution with a wet and dry vacuum.
- Apply one or two coats of **Nueva** sealer depending on application method and porosity of floor. Make sure you cross each coat, using a wet mop head or a mop especially designed for your sealer of finish.
- Allow to dry then apply one of our floor finishes

OPTIONAL: If dirty solution is picked up with a mop instead a vacuum, two rinses are recommended.

SPECIFICATION DATA

Total solids: (%)	19% +/- 1	RESISTANCE	
pH	8.5 - 9.5	Water	Excellent
Specific gravity:	1.02 - 1.03	Detergent	Excellent
Appearance	Transparent liquid	Drying	20 to 30 minutes
Colour of emulsion:	White	Flaking:	None
Film colour	Transparent	Buff-ability	Non- buff able
Gloss:	Very good	Stripping	Easy to strip with
Storage stability	12 months at 23.8 °C (75 °F)	Slip resistance	Non slip
Coverage	Freeze/Thaw: 3 cycles Approx. 350 meters		

CAUTION

Keep out of reach of children Avoid freezing.

PACKAGING

4 x 4 litres / 20 litres / 210 litres