

S-693 Premixed Sanded Acrylic Grout "Product Information"

**Caution/Warning**

 **Caution Eye and Skin Irritant**

**Caution / Warning**

See attachment below for procedures for grouting Alterna Tile.

**MSDS**

[MSDS Material Safety Data Sheet](#)

**Product Attributes**

**Product Attributes**

Description	
Type	Premixed sanded acrylic grout
Color	Available in a variety of colors
Taggants	None
Float	Hard epoxy
Coverage for 12" x 12" (30.5 cm x 30.5 cm) Tile	Quarts
	84 sq. ft./qt. (2.6 sq. m./946 mL) with 1/16" joint spacing 61 sq. ft./qt. (1.9 sq. m./946 mL) with 1/8" joint spacing 52 sq. ft./qt. (1.6 sq. m./946 mL) with 3/16" joint spacing 42 sq. ft./qt. (1.3 sq. m./946 mL) with 1/4" joint spacing
	Gallons
	338 sq. ft./gal. (10.4 sq. m./3.78 L) with 1/16" joint spacing 244 sq. ft./gal. (7.5 sq. m./3.78 L) with 1/8" joint spacing 206 sq. ft./gal. (6.3 sq. m./3.78 L) with 3/16" joint spacing 169 sq. ft./gal. (5.2 sq. m./3.78 L) with 1/4" joint spacing
Coverage for 16" x 16" (41 cm x 41 cm) Tile	Quarts
	112 sq. ft./qt. (10.4 sq. m./946 mL) with 1/16" joint spacing 81 sq. ft./qt. (7.5 sq. m./946 mL) with 1/8" joint spacing 68 sq. ft./qt. (6.3 sq. m./946 mL) with 3/16" joint spacing 56 sq. ft./qt. (5.2 sq. m./946 mL) with 1/4" joint spacing
	Gallons
	450 sq. ft./gal. (41.8 sq. m./3.78 L) with 1/16" joint spacing 325 sq. ft./gal. (30.2 sq. m./3.78 L) with 1/8" joint spacing 275 sq. ft./gal. (25.5 sq. m./3.78 L) with 3/16" joint spacing 225 sq. ft./gal. (20.9 sq. m./3.78 L) with 1/4" joint spacing
Units	1 quart (946 mL) and 1 gallon (3.78 L)
Open Time	Approximately 3-8 minutes
Working Time	Up to 10 minutes (working times may vary based on jobsite conditions, substrates, temperature and humidity)
Shelf Life	2 years, unopened

Freeze/Thaw Stable	No, keep from freezing
VOC Content	15 g/L; calculated and reported, SCAQMD 1168
Clean Up	Use clear cool water and a sponge. Do not allow grout to dry on face.
Advantages	Premixed-ready to use Resists cracking Color consistent Stain resistant Easy clean up

FEATURE	BENEFIT
<ul style="list-style-type: none"> <li>• Uniform color</li> </ul>	<ul style="list-style-type: none"> <li>• Consistent color throughout the floor</li> <li>• Cleaner layout</li> </ul>
<ul style="list-style-type: none"> <li>• Flexibility</li> </ul>	<ul style="list-style-type: none"> <li>• Minimizes cracking with slight movements in the floor</li> </ul>
<ul style="list-style-type: none"> <li>• Stain-resistant</li> </ul>	<ul style="list-style-type: none"> <li>• Easier to maintain</li> <li>• Grout cleans to its original color</li> </ul>
<ul style="list-style-type: none"> <li>• Premixed formula</li> </ul>	<ul style="list-style-type: none"> <li>• No mixing required, can use right away, less mess</li> </ul>
<ul style="list-style-type: none"> <li>• Cleans up easily with water</li> </ul>	<ul style="list-style-type: none"> <li>• Saves time on installation</li> </ul>
<ul style="list-style-type: none"> <li>• Can use for 1/16", 1/8", 3/16" and 1/4" joint widths</li> </ul>	<ul style="list-style-type: none"> <li>• Provides more layout options</li> </ul>
<ul style="list-style-type: none"> <li>• No sealing required</li> </ul>	<ul style="list-style-type: none"> <li>• Saves time on installation, saves money - no need to purchase sealers</li> </ul>
<ul style="list-style-type: none"> <li>• Ready for light traffic in 24 hours</li> </ul>	<ul style="list-style-type: none"> <li>• Less disruption to household</li> </ul>

**MANUFACTURING LOCATIONS:** N/A

**Order & Warehouse Information**

Order & Warehouse Information

Order and Warehouse Information	
Language	English
Size	1-quart 1-gallon
Carton Dimensions	1-quart -19.313" L x 14.125" W x 5" H 1 gallon - 15.5" L x 15.5" W x 7.75" H

<b>Carton Weight</b>	1-quart - 124 lbs 1-gallon - 46 lbs		
<b>Items per Carton</b>	1-quart - 12 1-gallon - 4		
<b>Cartons per Pallet</b>	1-quart - 36 1-gallon - 36		
<b>Weight per Gallon</b>	1-quart - 1.75 lbs 1-gallon - 12.59 lbs		
<b>Color Name / Number</b>	<b>Quart Item Number</b>	<b>Gallon Item Number</b>	<b>UPC for Carton</b>
Glacier / A1	693124A	693408A	1-quart - 042369734509 1-gallon - 10042369536636
Smoke / B2	693124B	693408B	1-quart - 042369734516 1-gallon - 10042369536643
Sandalwood / C3	693124C	693408C	1-quart - 042369734523 1-gallon - 10042369536650
Mushroom / D4	693124D	693408D	1-quart - 042369734530 1-gallon - 10042369536667
Gypsum / E5	693124E	693408E	1-quart - 042369734547 1-gallon - 10042369536674
Driftwood / F6	693124F	693408F	1-quart - 042369734554 1-gallon - 10042369536681
Cocoa / G7	693124G	693408G	1-quart - 042369734561 1-gallon - 10042369536698
Shale / H8	693124H	693408H	1-quart - 042369734578 1-gallon - 10042369536704
Sea Shell / I9	693124I	693408I	1-quart - 042369734585 1-gallon - 10042369536711
Mist / J10	693124J	693408J	1-quart - 042369734592 1-gallon - 10042369536728
Silver Cloud / K11	693124K	693408K	1-quart - 042369844222 1-gallon - 042369844208
Corn Silk / L12	693124L	693408L	1-quart - 042369844239 1-gallon - 042369844215

### Substrates

Substrates For use with Armstrong groutable vinyl tile.

### Installation Procedures

For use with the following Installation Systems:

#### Installation Procedures

- [Rounded Edge Tile Grouting Instructions](#)
- [CeraRoma Groutable Tile Installation](#)

- [Alterna Installation System](#)

**LEED / Environmental**

**LEED / Environmental** [LEED Credit Information - Installation Products](#)

**Warranty**

Armstrong warrants that this product will be free from manufacturing defects and will not break down or deteriorate under **Warranty** normal usage when used in accordance with our Product Specification Sheet and our installation and maintenance instructions, applicable building codes and regulations, and standard industry practices.

**Product Image**



Product Image