




The Strong System

Subfloor Preparation Products

The Strong System is a collection of subfloor preparation products suitable for the rigorous demands of commercial installations.

- Extend your Armstrong Flooring Guaranteed Installation System warranty coverage and length by 10 years
- Build your customized Strong System by selecting à la carte the preparation products that meet the needs of your project
- Save time and help ensure a successful installation by sourcing subfloor preparation products, adhesive, flooring, and maintenance supplies from a single source

The Strong System Warranty



The Strong Lineup



S-462 Seal Strong™

- A two-part moisture mitigation system designed to create a moisture barrier between concrete and resilient flooring
- Suitable for use up to 100% RH (or 25 lbs CaCl)
- Only one coat required to fully seal a concrete substrate
- Covers approximately 250 -270 sq. ft. per unit (at 10 mils)



S-466 Patch Strong™

- High performance patching and smoothing compound with quick drying time
- A true featheredge finish
- Easy to apply with smooth trowel skim coat application
- No RH limit for use over concrete
- Suitable for use over S-462 Seal-Strong after S-465 Prime Strong non-porous application
- No additive needed; easy to mix with water
- Zero VOC



S-463 Level Strong™

- A self-leveling underlayment designed to work quickly
- High compressive strength of 5300 psi
- Unaffected by concrete moisture up to 99% RH
- Installs up to 1-1/2" thick on porous substrates and up to 1/2" thick on non-porous substrates
- Ready for foot traffic in 2-3 hours



S-464 Prime Strong™


- Acrylic primer for porous substrates
- Aids in strengthening adhesive bond
- Helps to reduce subfloor porosity and absorbency
- Approved for use with all Armstrong Flooring resilient adhesives
- Low VOC



S-465 Prime Strong™

- Solvent-free, two-component primer for non-porous substrates
- Suitable for use over S-462 Seal -Strong and other non-porous substrates
- Ready for installation in as little as 3 hours
- Approved for use with all Armstrong Flooring resilient adhesives
- Low VOC

The Strong Overview



Use S-466 Patch Strong for repairing damaged areas that exceed CSP #6 Dormant hairline cracks of up to 1/32" can be covered with S-462 Seal Strong. Dormant joints and dormant cracks greater than 1/32" that will not be honored must be pre-filled with a highly fluid 100% rigid-drying crack filling material such as Ardex ArdFix™ intended for this purpose.

