

BLACK JACK[®]

70-026
70-026-XL

FLOATING FLOOR CUSHION UNDERLAYMENT


**Underlayment for laminate
and engineered wood floors**

COMFORT
2.5 mm foam provides
optimal floor cushion


PROTECTION
Includes adhesive strip for
easy installation and overlap
film to seal out moisture

LONG LASTING
Anti-crush technology for shock
absorption and long life


IIC STC Δ
70 | 66 | 21



Sound Reduction



Moisture Protection



Cushions Flooring



Mold Protection

IIC and STC tests measure sound transference from an upper level room to a lower level room. The IIC measures sound such as moving furniture and walking, while the STC measures sound such as voices and television. Minimum sound rating required by most building codes and architects is 50. Δ Delta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

Black Jack Floating Floor Cushion Underlayment[®] is a dense foam underlayment that helps absorb everyday in room noise under laminate and engineered flooring. The closed cell foam design is moisture resistant and fights against mold and mildew.

Scan here for
PRODUCT
INFORMATION



SPECIFICATIONS

ITEM #	70-026	70-026-XL
UNIT OF MEASURE	12 rolls / case	2 rolls / case
COVERAGE	100 sq. ft. / roll 1200 sq. ft. / case	600 sq. ft. / roll 1200 sq. ft. / case
WIDTH OF ROLL	43"	43"
LENGTH OF ROLL	28 ft.	167.5 ft.
THICKNESS	2.5 mm	2.5 mm
WEIGHT PER ROLL	1.95 lbs.	11 lbs.
DIAMETER OF ROLL	6.75"	16"