

70-177

 **ROBERTS**



ThermaWave TM *Plus*

Acoustical Barrier & Insulator Underlayment

EFFICIENT

Includes adhesive strip and 3" overlap film for linking multiple rolls

THERMAL INSULATION

Aluminum backing provides thermal insulation

UNIQUE DESIGN


Folding design eliminates curling and re-rolling

SOUND REDUCTION


Dense 2mm foam designed for supreme sound reduction and shock absorption

MOISTURE PROTECTION


Vapor Barrier Film for extra moisture protection and resistance to mold and mildew




Sound Reduction




Thermal Barrier




Moisture Protection



Cushions Flooring



Levels Imperfections



Radiant Heat

Thermawave's unique folding design eliminates corner curling and re-rolling, allowing for easier, faster installation. Its aluminum backing provides moisture protection and thermal insulation, while its dense 2mm foam provides excellent sound reduction. Ideal for the floating installation of laminate, engineered and click lock bamboo flooring.

For Canadian distribution only.

SPECIFICATIONS

UNIT OF MEASURE	12 per case
COVERAGE	100 sq. ft.
WIDTH	43.5 in.
LENGTH	27.8 ft.
THICKNESS	2 mm
WEIGHT	1.7 lbs. each
IIC	69
STC	65

J1215-9287

Quality & Excellence Since 1938.

www.ROBERTSCONSOLIDATED.com

U.S. Headquarters
866 435 8665

Canada
800 840 9422

Europe/Middle East
0031 24 6485348

Australia
011 61 3 9797 1888

New Zealand
64 9 415 9700