



8200

SUPERIOR

QUICKBOND

Spray Adhesive For Carpet Pads & More!

1. PRODUCT NAME

ROBERTS® 8200 Quick-Bond Spray Adhesive For Carpet Pads & More!

2. MANUFACTURER

Roberts Company Canada, Ltd.

34 Hansen Road South Brampton, ON L6W 3H4 (866) 435-8665 / (905) 791-4444

3. DESCRIPTION

ROBERTS 8200 Quick-Bond Spray Adhesive is a fast tacking aerosol adhesive with the versatility to be used on a wide array of substrates. It is formulated to bond carpet pad to porous and non-porous substrates, plus paper, cardboard, fabric, leather, foil, fiberglass to metal, drywall, masonry, wood and a variety of other substrates.

Features and Benefits

- · Fast tack, fast grab web spray
- · Low soak-in with high bond strength
- · Permanent or repositionable bond
- Does not contain chlorfluorocarbons (CFC's), ozone depleting chemicals, or methylene chloride

Uses

Bonding carpet pad, carpet and carpet repair, plus paper, cardboard, fabric, leather, foil, fiberglass to metal, drywall, masonry, wood, including polyurethane insulation blocks, insulation, polyethylene film, sanding discs and bead boards.

Coverage

Approximately 7.4-9.2 m^2 per 340 g / 80-100 ft² per 12 ounce.

Substrates

Porous and non-porous surfaces, concrete, APA rated plywood, one layer of well bonded, existing VCT (free of wax/finish), primed gypcrete (refer to ASTM F2419) and terrazzo.

Limitations

- Not recommended for unsupported vinyl fabric. Certain plastic and
 elastomeric substrates can exhibit bond failure due to plasticizer migration.
 Combinations of high temperature and humidity can promote bond failure.
 For nonmetallic substrates, testing of production parts in typical operating
 environments for compatibility and performance is recommended.
- Store indoors only. Combinations of high temperature and humidity can promote bond failure. For nonmetallic substrates, testing for compatibility and performance of production parts in typical operating environments is recommended.
- EXTREMELY FLAMMABLE. Vapors will accumulate readily. Keep product away from heat, sparks, flames, pilot lights, and sources of static discharge. Do not store above 120°F/49°C, or in direct sunlight. Contents under pressure. Do not puncture, incinerate or discard in compactor.
- Ensure adequate ventilation during flooring installation.
- Refer to Safety Data Sheet, www.robertsconsolidated.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.





4. TECHNICAL DATA

Product Type:	Web Spray Adhesive
Colour:	White
Odour:	Mild
Working Time:	Up to 4 hours
Tack Time:	Up to 2 minutes
VOC:	89 g/L
Shelf Life:	1 year in unopened container
Storage:	Protect from freezing

5. INSTRUCTIONS

Preparation

Surface must be structurally sound, dry and free from dirt, dust, old adhesive, wax, oil or grease.

Application

Shake well before using. Hold can 8 to 12 inches from surface to be sprayed and keep can moving to achieve an even coat of adhesive. For a permanent bond spray both surfaces, allow adhesive to dry to a tack and bond. For a temporary or repositionable bond, spray one surface only.

Curing

High temperature and low humidity will cause the adhesive to cure faster.

Clean-up

Dried adhesive – rub off or use mineral spirits sparingly with a clean, white cotton cloth. DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.

6. AVAILABILITY

Packaging

240 a / 12 H C ounce Carey Con	8200RB355	075378820017
340 g / 12 U.S. ounce Spray Can	020000333	0/33/002001/

7. WARRANTY

5-Year Direct Bond

ROBERTS warrants that this product will be free from manufacturing defects for 12 months from the date of manufacture, when applied in accordance with ROBERTS' instructions and industry standards. ROBERTS' sole liability is to either supply new product or refund the original purchase price. This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose. Any implied warranties arising by operation of law are limited to one year. ROBERTS will not be liable for any incidental or consequential damages.

Visit www.robertsconsolidated.com for full warranty details.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (905) 791-4444 or visit robertsconsolidated.com.

10. FILING SYSTEM

Division 9

 $ROBERTS@is a registered\ trademark\ of\ Roberts\ Consolidated\ Industries, Inc. \bullet Q.E.P.@is\ a\ registered\ trademark\ of\ Q.E.P.\ Co., Inc.\ Anti-Appendix and Appendix and$

