



Safety Data Sheet

Revision Date: 03/08/2018

SECTION 1: Identification and Company Details

Product Name: Roberts 8200 QuickBond Spray Adhesive
Product Code: 8200
Manufacturer/ Supplier: Roberts Canada Ltd.
Address: 34 Hansen Road S.
Brampton, ON L6W 3H4

Phone: (905) 791-4444 9am-5pm EST
Emergency Phone: (888) 226-8832 (CANUTEC) 24 hour response
Recommended Use: Adhesive

SECTION 2: Hazard(s) Identification

OSHA / HCS Status: This material is considered hazardous by the OSHA Hazard. Communication Standard (29 CFR 1910.1200)

Physical hazards:	Flammable aerosols	Category 1
	Gases under pressure	Liquefied Gas
Health Hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effect
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1

OSHA defined hazards: Not Classified

Signal Word: Danger

Hazard Statements: Extremely flammable aerosol
Contains gas under pressure; may explode if heated
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of damaging unborn child
Suspected of damaging fertility
May cause damage to organs through prolonged or repeated exposure



Hazard Pictograms:

Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/ doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards: Hazardous to the aquatic environment, acute Category 3
Hazardous to the aquatic environment, long term hazard Category 3

Hazard(s) not otherwise
Classified (HNOC): None known.
Supplemental information: None.

SECTION 3: Composition / Information on Ingredients

	<u>Weight %</u>	<u>CAS #</u>
Acetone	20 – 40	67-64-1
Propane	20 – 40	74-98-6
Dimethyl Ether	10 - 20	115-10-6
n-Hexane	10 - 20	110-54-3
2-Methylpentane	2.5 – 10	107-83-5
3-Methylpentane	1 - 2.5	96-14-0
Other components below reportable levels	10 - 20	

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: Not likely, due to the form of the product. Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/
Effects, acute and delayed: Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5: Fire-Fighting Measures

Extinguishing Media: Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing Media: **DO NOT** use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising From the chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Protection of Firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face-shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting equipment/
Instructions: In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific Methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards: Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SECTION 6: Accidental Release Measures

- Personal Precautions:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
- Environmental Precautions:** Small spills: wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
- Methods of Clean-up:** Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

SECTION 7: Handling and Storage

- Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
- Conditions for Safe Storage:** Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8: Exposure Control / Personal Protection

OCCUPATIONAL EXPOSURE LIMITS:

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m ³ 500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US ACGIH Threshold Limit Values

Components	Type	Value
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm
Acetone (CAS 67-64-1)	TWA STEL	500 ppm 500 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm

US NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3 50 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

US Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Dimethyl Ether (CAS 115-10-6)	TWA	1800 mg/m3 1000 ppm

BIOLOGICAL LIMIT VALUES:

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

EXPOSURE GUIDELINES

US - California OELs - Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values - Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate Engineering Controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual Protection Measures:

Eye/Face Protection:

Wear safety glasses with side shields (or goggles).

Hand Protection:

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin Protection:

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory Protection:

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards:

Wear appropriate thermal protective clothing, when necessary.

General Hygiene:

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/ or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and Chemical Properties

Appearance:	Gas. Aerosol, liquefied gas
Vapor Density:	Not determined
Odor:	Not determined
Relative Density:	Not determined
Odor Threshold:	Not determined

Solubility(ies):	Not determined
pH:	Not determined
Partition Coefficient:	Not determined
Melting Point:	Not determined
Freezing Point:	Not determined
Auto-ignition Temperature:	Not determined
Flash Point:	> 156° F (-104.4 °C) PROPELLANT estimated
Decomposition Temperature:	Not determined
Evaporation Rate:	Not determined
Viscosity:	Not determined
Flammability (Solid/Gas):	Not determined
Specific Gravity:	0.724 estimated
Upper/Lower Flammability:	Lower 2.5% estimated – upper 10.2% estimated
Vapor Pressure:	62 psig @70F estimated
Initial Boiling Point and boiling range:	32.1 °C (89.77° F) estimated
VOC (weight %):	53% estimated

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	Hazardous polymerization does not occur.
Conditions to Avoid:	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decomposition Products:	No hazardous decomposition products are known.

SECTION 11: Toxicological Information

Acute Toxicity:	May be fatal if swallowed and enters airways. Narcotic effects.
Ingestion:	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation:	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact:	Causes skin irritation.
Eye contact:	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea Pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Dimethyl Ether (CAS 115-10-6)		

Acute		
Inhalation		
NOEL	Rat	2 ppm, 6 Hours
n-Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
Inhalation		
LC50	Rat	> 5000 ppm, 24 Hours > 31.86 mg/l 73860 ppm, 4 Hours
Oral		
LD50	Rat	24 ml/kg 24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

*Estimates for product may be based on additional component data not shown

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Germ cell mutagenicity

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure

Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Toxic to aquatic life with long lasting effects.

COMPONENT - Acetone (CAS 67-64-1)

Category : Aquatic

		Species	Test Results
Crustacea	EC50	Water flea (Daphnia Magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow Trout, Donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

COMPONENT - Dimethyl Ether (CAS 115-10-6)

Category: Aquatic

		Species	Test Results
Crustacea	EC50	Water flea (Daphnia magna)	4.3 - 7.8 mg/l, 48 hours

Fish	LC50	Striped bass (<i>Morone saxatilis</i>)	10.302 - 16.743 mg/l, 96 hours
------	------	------------------------------------------	--------------------------------

COMPONENT - n-Hexane (CAS 110-54-3)

Category		Species	Test Results
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	2.101 - 2.981 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and Degradability: No data is available on the degradability of this product.

Bioaccumulative Potential:

Partition Coefficient n-octanol / water (log Kow):

2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Dimethyl Ether	0.1 n-
Hexane	3.9
Propane	2.36

Mobility in Soil: No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal Considerations

Disposal Instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local Disposal Regulations	Dispose in accordance with all applicable regulations.
Hazardous Waste Code:	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from Residue/Unused Product:	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated Packaging:	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14: Transport Information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable (each not exceeding 1 L capacity)
Transportation Hazard Class:	Class 2.1 Subsidiary risk - None Label 2.1
Special precautions for user:	Read safety instructions, SDS and emergency procedures before handling.
Special Provisions:	N82
Packaging Exceptions:	306
Packaging Non Bulk:	None
Packaging Bulk:	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages

of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable Class 2.1
Transport hazard class(es)	
	Subsidiary risk - Label(s) 2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user:	Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo aircraft	Allowed with restrictions.
------------------------------	----------------------------

Other information	
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS Class 2.1
Transport hazard class(es)	
	Subsidiary risk - Label(s) None
Packing group	Not applicable.
Marine pollutant	No.
Environmental hazards	
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT



IATA; IMDG



General information:	Avoid Transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 15: REGULATORY INFORMATION

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4): Acetone (CAS 67-64-1) Listed.
n-Hexane (CAS 110-54-3) Listed.

SARA 304 Emergency Release Notification: Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.
Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard Categories:
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No
SARA 302 Extremely Hazardous Substance: Not listed
SARA 311/312 Hazardous: None

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt
n-Hexane	110-54-3	10 - 20

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: n-Hexane (CAS 110-54-3)
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention
(40 CFR 68.130): Dimethyl Ether (CAS 115-10-6) Propane (CAS 74-98-6)
Safe Drinking Water Act (SDWA): Not regulated
Drug Enforcement Administration (DEA). List 2, Essential Chemicals
(21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number: Acetone (CAS 67-64-1) 6532
Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical

Mixtures (21 CFR 1310.12(c)): Acetone (CAS 67-64-1) 35 %WV
DEA Exempt Chemical Mixtures Code Number: Acetone (CAS 67-64-1) 6532

State Regulations:

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)
Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)
n-Hexane (CAS 110-54-3)

US. Massachusetts RTK - Substance List

2-Methylpentane (CAS 107-83-5)
Acetone (CAS 67-64-1)
Dimethyl Ether (CAS 115-10-6)
n-Hexane (CAS 110-54-3)
Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Methylpentane (CAS 107-83-5)
Acetone (CAS 67-64-1)
Dimethyl Ether (CAS 115-10-6)
n-Hexane (CAS 110-54-3)
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Methylpentane (CAS 107-83-5)
Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Dimethyl Ether (CAS 115-10-6)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

Inventories:

All components are on the Canadian DSL or exempt.

All components of this product are on the US TSCA inventory

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Hazardous Products Regulation (WHMIS 2015)

Prepared by: Roberts Product Safety & Regulatory Compliance Group, (905) 791-4444

The information herein is given in good faith, but no warranty expressed or implied is made. Roberts urges users of this product to evaluate its suitability and compliance with local regulations as Roberts can neither foresee the final use of the product, nor the final location of usage.

Date of issue: 03/08/2018