



# Hardwood Installation Products

**ADHESIVES, MOISTURE CONTROL, SOUND ABATEMENT,  
SURFACE PREPARATION AND ACCESSORIES**



# Bostik is innovating in all markets

- 1 **Aerospace:** Polymers with exceptional properties for the extreme demands of aircraft interiors
- 2 **Flexible Packaging:** Adhesives capable of withstanding the rigors of the flexible packaging industry
- 3 **Non-Wovens:** Super-absorbent polymers & elastic adhesives, improving comfort and well-being
- 4 **Automotive:** Ultra-high performance adhesives for composites used in modern vehicles
- 5 **Resealable Adhesives:** Meeting the growing consumer demand for convenience and sustainability
- 6 **Construction:** Adhesives, grouts, sealants and other construction products revolutionizing the industry
- 7 **Window, Siding & Door:** The preferred choice of many window, siding & door manufacturers worldwide
- 8 **Marine:** Offering a premium line of adhesives and sealants for the marine industry
- 9 **Industrial Lamination:** Innovative bonding solutions that enhance the capabilities of customer's end product



## ARKEMA

INNOVATIVE CHEMISTRY

### Advanced by Arkema For the Ultimate Bond Between Art & Science

For decades, Bostik's products have created literal bonds between surfaces and building components, all while supporting distinctive design. Together, with our parent company, Arkema—a global leader in specialty chemicals and advanced materials—that bond is reinforced.

Bostik's promise to specifiers is backed by three hubs on three continents, thirteen R&D centers worldwide and the same culture of innovation that supports Kynar® fluoropolymer coatings, Rilsan® high-performance polyamides and Plexiglas® acrylic sheet and resin products. Looking ahead, you can rest assured that our bond is just as durable as our adhesives.

KYNARAQUATEC  
BY ARKEMA

RILSAN®  
FINE POWDERS  
BY ARKEMA

PLEXIGLAS®  
BY ARKEMA



# Table of Contents

---

## **Inside Our Technology**

Tech Feature: Moisture Vapor Control	4
Hardwood Reference Guide	5

## **Axios® Tri-Linking™ Products**

Tech Feature: Thickness Control™ Spacers	6
Ultra-Set® SingleStep2™	7
Greenforce®	9

## **Bostik Pro Rewards**

Rewards Program Overview	8
--------------------------	---

## **Hardwood Adhesives & Moisture Protection**

Vapor-Lock™	10
Bostik's BEST®	10
Tech Feature: SoundGuard™	11
EFA+™	12
BST™	12
Pro-MSP™	12
Pro-Cure™	12
Wood-Tack™	13

## **Tech Feature**

Bostik's Smart App	13
--------------------	----

## **Moisture Vapor Barriers**

MVP4®	13
-------	----

## **Cartridge Products**

Climb™	14
915FS™	14
HeavyDuty™	14
955-SL™	14

## **Accessories**

Ultimate™ Adhesive Remover	15
Cartridge Guns	15



# Experiencing moisture issues?

## We're here to help.

### The hardwood industry's most trusted line of moisture vapor control products.

Bostik, the leader in hardwood adhesives, offers the most comprehensive range of products featuring unlimited moisture vapor protection with **no concrete moisture testing requirements**. Also, with these Bostik adhesives there are never any board width or length restrictions, making it easier for you to install your hardwood flooring. The formulas you trust, and the performance you can rely on.

#### Adhesive Comparison



Moisture Warranty And Duration	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited	Lifetime, Unlimited*
Flooring Types Covered	Solid, Engineered, Bamboo	Solid, Engineered, Bamboo	Solid, Engineered (Bamboo 15 lb/87% RH limit)	Engineered	Solid, Engineered, Bamboo
Sound Guard™ Sound Reduction	70 IIC, 67 STC	--	69 IIC, 66 STC	--	62 IIC, 52 STC

\* Axios®, Urethane, or MS-Polymer  
\*\* When used with any Bostik adhesive.

# HARDWOOD

## Reference Guide

	Ultra-Set® SingleStep2™	Vapor-Lock™	GreenForce®	Bostik's BEST®	BST™	Pro-MSP™	EFA+™	Pro-Cure™	Wood-Tack™
<b>Product Trait</b>									
Axios® Tri-Linking™ Technology	✓	--	✓	--	--	--	--	--	--
Moisture limits (Max MVER)	Unlimited	Unlimited*	Unlimited	Unlimited***	6 lb	10 lb	6 lb	--	--
Moisture warranty	Lifetime	Lifetime	Lifetime	Lifetime	5 years	5 years	5 years	--	--
Warranty without moisture vapor testing	✓	--	✓	--	--	--	--	--	--
Sound abatement (IIC/STC)	70/67	69/66	--	--	--	--	--	--	--
Thickness Control™ Spacer Technology	✓	✓	--	--	--	--	--	--	--
Easy clean after cure	✓	--	✓	--	--	✓	--	--	--
Workability	Excellent	Moderate	Excellent	Moderate	Moderate+	Easy	Easy	Moderate	Excellent
Green grab	Strong	Strong	Good	Good	Strong	Moderate	Moderate	Moderate	Good
Unit size	4 gallon	4 gallon	4 gallon, 12 x 28 oz	5 gallon, 12 x 28 oz, 24 x 10.1 oz, 12 x 10.1 oz	4 gallon	4 gallon	5 gallon	4 gallon	4 gallon
<b>Warranty</b>									
Duration of Bond Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	10 year	10 year
Moisture Warranty Duration	Lifetime	Lifetime	Lifetime	Lifetime	5 Years	5 Years	5 Years	--	--
Flooring Types Under Moisture Protection Warranty	Solid, Bamboo, Engineered	Solid, Engineered	Solid, Bamboo, Engineered	Engineered	Engineered	Solid, Bamboo, Engineered	Engineered	--	--
<b>Cured Physical Properties</b>									
Concrete Moisture Vapor Limits	None, Dry to the Touch	None, Dry to the Touch*	None, Dry to the Touch	None, Dry to the Touch*	≤ 6 lb or 80% RH	≤ 10 lb or 85% RH	≤ 6 lb or 80% RH	≤ 3 lb or 75% RH	≤ 3 lb or 75% RH
Contains Bostik's Blockade®	Yes	Yes	Yes	Yes	No	No	No	No	No
<b>Sound Reduction Performance</b>									
ASTM E2179 Increased Impact Insulation	21 dB	21 dB	--	--	--	--	--	--	--
ASTM E492-04 IIC-6" Slab With 5/8" Gypsum Ceiling	70	69	--	--	--	--	--	--	--
ASTM E90-09 STC-6" Slab With 5/8" Gypsum Ceiling	67	66	--	--	--	--	--	--	--
<b>Application Properties</b>									
Ease of Troweling	Excellent	Good	Excellent	Good	Moderate	Easy	Easy	Moderate	Excellent
Color	Beige w/ Black Specs	Brown w/ Black Specs	Beige	Tan	Brown	Brown	White	Beige	Beige/Tan
Density (lbs/gallon)	14.25	14.7	14.25	12.66	12.66	14.25	13.7	14.08	10.26
<b>Chemical Properties</b>									
Chemistry Type	AXIOS® Tri-Linking™	Urethane	AXIOS® Tri-Linking™	Urethane	Urethane	MS Polymer	Urethane	Urethane	Water-based
VOC Compliant (calculated per SCAQMD Rule 1168)	Yes (0 g/L)	Yes (0 g/L)	Yes (0 g/L)	Yes (20 g/L)**	Yes (22 g/L)**	Yes (8 g/L)**	Yes (25 g/L)**	Yes (25 g/L)**	Yes (10 g/L)
<b>LEED® Point Contributions</b>									
EQ 4.1: Low-Emitting Materials—Adhesives & Sealants	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
MR 4.2: Recycled Content	Yes, 1% by Weight	Yes, 1% by Weight	No	No	No	No	No	No	No


\*Vapor-Lock™ moisture limit for bamboo: ≤15 lb or 85% RH \*\*Tested per EPA Method 24.  
 \*\*\*Unlimited moisture limits for Bostik's BEST® applies only to engineered hardwood flooring



## TECH FEATURE

# Reduce Risk, Improve Installations

## Focus on Bostik's Thickness Control™ Spacer Technology




At Bostik, innovation comes in many forms, not just chemistry. Bostik's patent-pending Thickness Control™ Spacer Technology is a proprietary feature that helps ensure proper membrane thickness is maintained between the hardwood flooring and substrate. Installers can use mallets to engage the tongue and groove or even walk on their work during the installation process without significant reduction in the film thickness that could compromise moisture protection or sound control.

The key is in the rubber crumbs mixed in with the adhesive. The particles are made of recycled, ground up car tires. The size of the particles creates the optimal membrane thickness for superior performance as a moisture reduction and sound control membrane. If you stand on a board installed over any adhesive using Thickness Control™ Spacers, the rubber particles prevent the fluid adhesive from squeezing out underneath the boards and the desired membrane thickness is maintained.

Bostik's Thickness Control™ Spacer Technology not only reduces your risk of failing to achieve proper membrane thickness that could result in flooring failures from moisture, it also makes installation easier. You won't need a special trowel or a clip-on component that wears out quickly. You can use common trowels and be confident that you've got the moisture control and sound reduction performance you expect.





**EASY CLEAN BEFORE &  
AFTER CURE**

**UNLIMITED MOISTURE  
VAPOR PROTECTION**

**SUPERIOR SOUND  
REDUCTION PERFORMANCE**



**Bavette's Steakhouse**  
Park MGM, Las Vegas, NV

## ULTRA-SET® SINGLESTEP2™



### ADVANCED TRI-LINKING™ ADHESIVE, MOISTURE CONTROL & SOUND REDUCTION MEMBRANE

Ultra-Set® SingleStep2™ is a high performance adhesive, moisture control, and sound reduction membrane all in one. Bostik's breakthrough AXIOS® Tri-Linking™ Polymer Technology used in this formulation maintains the superior long term durability, moisture control and sound abatement properties of high end urethane adhesives. However, it is easier to spread and clean off of prefinished flooring before and after cure. This adhesive contains 1% recycled rubber material, has zero VOC's (as calculated per SCAQMD Rule 1168) and does NOT contain any water.



#### ULTRA-SET® SINGLESTEP2™

Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850854	4 gallon	36 pails	747224700001	--





# Bostik Pro Rewards™

## Contractor Loyalty Program

Now you can earn valuable reward points which can be redeemed for thousands of brand name items or travel rewards, all while growing your business!

To join the **Bostik Pro Rewards™** contractor loyalty program, visit: **[www.awardlink.com/Bostik](http://www.awardlink.com/Bostik)** where you'll be asked to create a user name and password for your account.


1. Register all eligible Bostik product purchases by submitting your invoices via our rewards program web portal.
2. All registered Bostik product purchases will automatically be deposited into your **Bostik Pro Rewards™** account.
3. Redeem the points you've earned for a wide variety of great rewards.



# JOIN NOW!

**[www.awardlink.com/Bostik](http://www.awardlink.com/Bostik)**





**EASY CLEAN BEFORE & AFTER CURE**

**UNLIMITED MOISTURE VAPOR PROTECTION**

**SUPERIOR BOND STRENGTH & GREEN GRAB**

## GREENFORCE®

### ADVANCED TRI-LINKING™ ADHESIVE & MOISTURE CONTROL MEMBRANE

GreenForce® is a high performance adhesive and moisture control membrane all in one. Bostik's breakthrough AXIOS® Tri-Linking™ Polymer Technology used in this formulation maintains the superior long term durability and moisture protection properties of high end urethane adhesives. However, it is easier to spread and clean off of prefinished flooring before and after cure. This adhesive has zero VOC's (as calculated per SCAQMD Rule 1168) and does NOT contain any water.



#### GREENFORCE™

Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850844	4 gallon	36 pails	747224700018	--
30850846	12 x 28 oz cartridge	60 cases	10747224700107	747224700100

# Vapor-Lock™

## HARDWOOD ADHESIVE, MOISTURE CONTROL & SOUND REDUCTION MEMBRANE

Bostik's Vapor-Lock™ is a high performance adhesive, moisture control, and sound reduction membrane all in one. Its superior properties provide a tough, flexible, tenacious bond to a variety of surfaces, and it is not adversely affected by exposure to moisture, water or alkalinity. When applied as directed as a moisture vapor membrane, it will prevent damages caused by high subfloor moisture vapor. As a result, costly and time consuming concrete moisture testing is not required for solid or engineered hardwood flooring. For bamboo flooring, Vapor-Lock™ may be used for concrete slabs with elevated moisture levels up to 15 lbs or 87% RH.

Vapor-Lock™ exhibits exceptional green grab or high tack immediately after troweling, making installation easier and more secure. This adhesive contains 1% recycled rubber material, has zero VOC's (as calculated per SCAQMD Rule 1168) and does NOT contain any water. Vapor-Lock™ contains Bostik's BLOCKADE™ antimicrobial protection, which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive.



# Bostik's BEST®

## WOOD FLOORING URETHANE ADHESIVE AND MOISTURE VAPOR CONTROL

Bostik's BEST® is a high performance adhesive and moisture control membrane. Its superior properties provide a tough, flexible, tenacious bond to a variety of surfaces. Bostik's BEST® high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure. When applied as directed as a moisture vapor membrane, it will prevent damages caused by high subfloor moisture vapor. As a result, costly and time consuming concrete moisture testing is not required for engineered hardwood flooring. For solid hardwood or bamboo on substrates >3 lbs. or 75% RH, use MVP4® prior to the use of Bostik's BEST®.

This adhesive has low VOC's (measured per EPA Method 24) and does NOT contain any water. Bostik's BEST® contains Bostik's BLOCKADE™ antimicrobial protection, which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive.



VAPOR-LOCK™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850864	4 gallon	36 pails	747224699312	--

BOSTIK'S BEST®				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Mfr Location
30850825	5 gallon	36 pails	747224389053	Conyers
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850116	12 x 28 oz cartridge	60 cases	10747224700121	747224700124
30850117	12 x 10.1 oz cartridge	96 cases	10747224700084	747224389107
30850115	24 x 10.1 oz cartridge	105 cases	10747224700060	747224389107





## Tech Feature

# Increase comfort and ease tensions... with adhesive?



Nobody wants to be disturbed by their neighbors. Whether it's the home theater system from your neighbors below, or the high heeled shoes of the neighbor above, acoustics play an essential role in the comfort of a home. Most local building codes have standardized on two methods of measuring noise. STC (Sound Transmission Coefficient) measures the airborne sound moving through a floor, and IIC (Impact Isolation Class) measures sound from impact on the floor. The International Building Code (IBC) requires a minimum of 50 dB for both IIC and STC.

Bostik offers several products specifically designed to improve acoustics and outperform typical 1/4" cork underlayments. Independent laboratory testing results are summarized on the table below.

Test*	Ceiling Type	Vapor-Lock™	Ultra-Set® SingleStep2™	MVP4™ + Adhesive**
IIC	5/8" Suspended Gypsum	69 dB	70 dB	62 dB
	No Suspended Ceiling	49 dB	50 dB	49 dB
Δ IIC	No Suspended Ceiling	21 dB	21 dB	21 dB
STC	5/8" Suspended Gypsum	66 dB	67 dB	61 dB
	No Suspended Ceiling	50 dB	51 dB	52 dB

\* Tests were performed using 3/8" engineered hardwood bonded to 6" thick concrete

\*\* Test performed with 9/16" thick engineered hardwood and Bostik's Best®.

Bostik installation systems are superior to most mats or underlayments used under floating floors, which may reduce sound between floors, but do not significantly reduce the sound of footsteps within the room. When there is an impact on a floating hardwood floor, the boards vibrate. Downward motion is absorbed, but the upward rebound is not. This results in a hollow sound in the flooring. Adhesives with sound abatement characteristics work to reduce the vibration of the boards in both directions resulting in a quieter floor, dramatically increasing the comfort of the space and virtually eliminating one of the most common complaints of multi-family living.

## EFA+™

### ELASTOMERIC FLOORING ADHESIVE & MOISTURE VAPOR RETARDER

Bostik's EFA+™ is an easy-to-trowel urethane adhesive and moisture control membrane. It provides a tough, flexible, tenacious bond to a variety of surfaces. Bostik's EFA+™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's EFA+™ exhibits a long open time, making installation easier and faster. This adhesive has low VOC's (as calculated per SCAQMD Rule 1168) and does NOT contain any water.

EASY SPREAD

GREAT RIDGE RETENTION

LOW VOC



## BST™

### WOOD FLOORING ADHESIVE & MOISTURE VAPOR RETARDER

Bostik's BST™ is a urethane adhesive and moisture control membrane. Its superior properties provide a tough, flexible, tenacious bond to a variety of surfaces. Bostik's BST™ elastomeric characteristics allow the adhesive to move with the wood as it expands and contracts over the life of the floor. Bostik's BST™ exhibits exceptional green grab making installation easier as it minimizes slipping of the flooring. This adhesive has low VOC's (as calculated per SCAQMD Rule 1168) and does NOT contain any water.

GREAT GREEN GRAB  
MINIMIZES SLIPPING

MODERATE MOISTURE  
VAPOR PROTECTION

LOW VOC



## Pro-MSP™

### HARDWOOD ADHESIVE WITH MOISTURE VAPOR PROTECTION

Pro-MSP™ is a hardwood and bamboo adhesive and moisture control membrane all in one. This adhesive formulation maintains long term durability and moisture control properties, and it is easy to spread and clean off of prefinished flooring before and after cure. This adhesive has low VOC's (as measured per EPA Method 24) and does NOT contain any water.

EASY SPREAD & CLEAN

SUBFLOOR MOISTURE  
PROTECTION

LOW ODOR & VOC



## Pro-Cure™

### MOISTURE-CURE URETHANE ADHESIVE

Bostik's Pro-Cure™ is a professional grade, moisture-cure urethane adhesive for wood flooring; this adhesive does NOT contain any water. Pro-Cure™ may be used to adhere all engineered, acrylic impregnated, solid plank-flat milled, shorts, bamboo and parquet hardwood flooring designed and recommended in writing by the hardwood flooring manufacturer for glue-down applications. This adhesive can also be used to install plywood as described, as well as, ceramic tile, marble, and stone inlays for light commercial and/or residential applications.

HIGH-PERFORMANCE  
URETHANE FORMULATION

FOR ALL GLUE-DOWN WOOD  
& BAMBOO FLOORING

EASY SPREAD & EASY CLEAN



EFA+™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850811	5 gallon	36 pails	747224626455	--
BST™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850806	4 gallon	36 pails	747224700278	--

PRO-MSP™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850809	4 gallon	36 pails	747224700209	--
PRO-CURE™				
Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30850842	4 gallon	36 pails	747224680402	--



# Bostik's smart app is now available!

**iOS & Android Device Compatible**

Download the **Bostik Construction USA** app from your iOS or Android device, or visit: [bit.ly/BostikUSApp](http://bit.ly/BostikUSApp) (case sensitive)



**HARDWOOD  
ADHESIVES**

**MOISTURE  
VAPOR BARRIERS**

## Wood-Tack™

**ENGINEERED WOOD FLOORING ADHESIVE**

Wood-Tack™ is an adhesive for engineered, solid, and select bamboo hardwood flooring installations. This air-curing, self-crosslinking adhesive is exceptionally easy to trowel, and its rapid tacking properties allow for fast installation of wood flooring materials. Wood-Tack™ is a low VOC, low odor adhesive that does not contain any solvents or heavy metals. This adhesive provides exceptional bond strength between the wood flooring and substrate.

**RAPID TACKING**

**FAST INSTALLATION IN ABOVE-  
GRADE APPLICATIONS**

**EXCEPTIONALLY EASY  
TO TROWEL**



### WOOD-TACK™

Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
30856391	4 gallon	48 pails	747224606723	--

## MVP4®

**MOISTURE VAPOR PROTECTION,  
ANTI-FRACTURE AND NOISE REDUCTION MEMBRANE**

Bostik MVP4® Moisture Vapor Protection is a one-part, trowel applied, elastomeric, moisture cure urethane membrane designed to be used beneath glue-down installations of engineered, solid and bamboo hardwood flooring with Bostik's Best®, BST™, EFA+™, or Vapor-Lock™ adhesives. Bostik MVP4® is designed to reduce moisture vapor transmission from the subfloor, create a noise reduction barrier over the substrate, and establish an anti-fracture membrane, which can bridge cracks that can occur in the substrate prior to or after installation (up to 1/8").

**PREVENTS DAMAGE CAUSED  
BY SUBFLOOR MOISTURE**

**BELOW, ON AND ABOVE  
GRADE INSTALLATIONS**

**EXCEEDS IRC REQUIREMENTS  
FOR VAPOR RETARDERS**



### MVP4®

Item No.	Size	Units/pallet	Pail/Case UPC Code	Cartridge UPC Code
308505841	5 gallon	36 pails	747224669001	--

# Climb™

## HARDWOOD WALL PLANK AND TREAD CAP ADHESIVE

Bostik Climb™ is a one-component, easy gunning, non-sag adhesive that is specifically formulated for hardwood flooring planks or blocks on interior, above-grade walls and installation of stair tread caps. The Climb™ formula has superior green grab (grab strength while wet) and cures quickly to form a tenacious bond. Once cured, Climb™ remains tough yet flexible for extreme durability, helps reduce stair squeaking, and reduces the sound of footsteps on the stairs. This specialty formulation is also easy to clean off of hardwood wall planks, prefinished tread caps and risers even after cure. Climb™ has 0% solvents and low odor.

EXTREMELY STRONG,  
DURABLE BOND

EASY TO CLEAN,  
EVEN AFTER CURE

HELPS ELIMINATE SQUEAKING  
& REDUCES SOUND



# Heavy Duty™

## CONSTRUCTION ADHESIVE

A one-component, moisture cure polyurethane adhesive exhibiting high strength and is suitable for both interior and exterior installations. Heavy Duty™ Construction Adhesive typically does not require priming to achieve a watertight seal on common construction materials such as stone, concrete, masonry, cedar, wood, anodized aluminum, galvanized steel, vinyl, fiber-cement board, etc. Heavy Duty™ Construction Adhesive can bond to wet, frozen or treated lumber.

REDUCES SQUEAKS  
IN SUB-FLOORS

95% SOLIDS AND FASTER CURE THAN  
TYPICAL SOLVENT-BASED SYSTEMS

ADHERES TO WET AND  
FROZEN LUMBER



### CLIMB™

Item No.	Color	Size	Barcode	Case Code
30854239	White	12 x 10.1 oz/case*	747224700292	10747224700299
Package Size		Weight/Unit	Units/Pallet	Weight/Pallet
10.1 oz cartridge		13.3 lbs/case	96	1,325 lbs

\*Sold in full cases only

### HEAVY DUTY™ CONSTRUCTION ADHESIVE

Item No.	Color	Size	Barcode	Case Code
30854485	Natural	12 x 10.1 oz/case*	747224699107	10747224699104
30850203	Natural	12 x 28 oz/case*	747224699206	10747224699203
Package Size		Weight/Unit	Units/Pallet	Weight/Pallet
10.1 oz cartridge		15 lbs/case	96	1,490 lbs
28 oz cartridge		26 lbs/case	60	1,610 lbs

\*Sold in full cases only

# 915FS™

## FAST SETTING POLYURETHANE SEALANT

A one-component, architectural grade, polyurethane sealant capable of dynamic joint movement totaling 50% of original joint geometry (±25%). It cures to a tough, flexible rubber when exposed to moisture present in the atmosphere. With its fast-setting, high strength, elastomeric properties and convenient packaging, 915FS™ is ideal for medallions, stair treads, borders, starter rows and trim. Its physical properties will remain relatively stable over time and in varying weather conditions and are relatively unchanged over a wide temperature range, -40°F to 150°F (-40°C to 66°C).

FAST SET, PERFECT FOR STARTER  
ROWS, STAIR TREADS & MEDALLIONS

NON-SAG, GREAT FOR  
TRIM & FLOOR REPAIR

EXCEPTIONAL JOINT  
MOVEMENT CAPABILITY



# 955-SL™

## SELF LEVELING POLYURETHANE SEALANT

A one-component, self-leveling, polyurethane sealant capable of dynamic joint movement totaling 70% of original joint geometry (±35%). The sealant cures to a tough, flexible rubber when exposed to moisture present in the atmosphere. 955-SL has a pourable consistency. Its physical and mechanical properties remain consistent across a broad temperature range, from -40°F to 150°F (-40°C to 66°C).

SELF LEVELING FORMULATION,  
NO TOOLING REQUIRED

CARB, OTC, SCAQMD  
COMPLIANT

SEALS CRACKS >1/8" FOR  
MOISTURE PROTECTION



### CAULKS, SEALANTS & ADHESIVES

Item No.	Size	Color	Barcode	Case Code
<b>915FS™</b>				
30850253	24 x 10.1oz/case*	White	747224900012	10747224900019
<b>955-SL™</b>				
30850206	12 x 28 oz/case*	Limestone	747224710109	10747224710106
Package Size		Weight/Unit	Units/Pallet	Weight/Pallet
24 x 10.1 oz cartridge		24 lbs/case	80	1,950 lbs
12 x 20 oz sausage		24 lbs/case	100	2,430 lbs
12 x 28 oz cartridge*		26 lbs/case	60	1,610 lbs

\*Sold in full cases only





To view Bostik's YouTube channel scan this code, or visit [youtube.com/bostikUSA](https://youtube.com/bostikUSA)



## Ultimate™

### ADHESIVE REMOVER

Use Bostik's Ultimate™ Adhesive Remover to remove wet and cured urethane adhesive from the surface of pre-finished (non-wax) wood flooring. Ultimate Adhesive Remover is a readily biodegradable, low-odor, water-rinsable solution. Bostik's Ultimate™ is available in two formulations: liquid and pre-soaked, ready-to-use towels.

READY TO USE

REMOVES CURED AND UNCURED URETHANE ADHESIVES

RESIDUE FREE



## Cartridge Guns

### CARTRIDGE DISPENSING GUNS

Bostik high quality cartridge guns are designed to last and to make your job easier. Our standard 7:1 drive is perfect for lower viscosity products like Simple-Fix™, while our deluxe 26:1 drive is perfect for the higher viscosity hardwood adhesives and construction sealants.

STANDARD 7:1 DRIVE FOR LOWER VISCOSITY PRODUCTS

DELUXE 26:1 DRIVE FOR VERY VISCOUS PRODUCTS

10.1 OZ AND 28 OZ SIZES



ACCESSORIES

#### ULTIMATE™ ADHESIVE REMOVER

Item No.	Item	Size	Units/pallet	Pail/Case UPC Code
30850832	Liquid	1 quart - 12/case	48 cases	747224656094
30612734	Towels	1 canister - 6/case	120 cases	747224656018

#### CARTRIDGE GUNS

Item No.	Size	Drive
30852242	Manual 10 oz	Standard 7:1 Drive
30852243	Manual 10 oz	Deluxe 26:1 Drive
30852244	Manual 28 oz	Deluxe 26:1 Drive

## Quick Links:

[bit.ly/BostikUSAYoutube](https://bit.ly/BostikUSAYoutube)

[bit.ly/AxiosTechnology](https://bit.ly/AxiosTechnology)

[bit.ly/DimensionGrout](https://bit.ly/DimensionGrout)

[bit.ly/GroutCalculator](https://bit.ly/GroutCalculator)

[bit.ly/BostikBinders](https://bit.ly/BostikBinders)

[bit.ly/BostikMSDS](https://bit.ly/BostikMSDS)



**Smart help:  
1-800-726-7845**

### **Bostik, Inc.**

11320 W. Watertown Plank Road

Wauwatosa, WI 53226

[www.bostik.com/us](https://www.bostik.com/us)

