

FINE IMPRESSIONS TILE

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Fine Impressions Tile /
PRODUCT TYPE	Carpet Tile
COLLECTION NAME	Translations
FIBER TYPE	Colorstrand SD Nylon
BACKING	UltraSet
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Textured Loop
DYE METHOD	Solution Dyed
INSTALLATION METHODS	QuarterTurn, BrickAshlar, VerticalAshlar, Monolithic, MultiDirectional
SIZE	24" x 24" (.6096 m x .6096 m)
THICKNESS	.082" (2.08 mm)
GAUGE	1/12 (47.00 rows per 10 cm)
STITCHES PER INCH	12.5 (49.21 per 10 cm)
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
DENSITY	6,673
FLAMMABILITY	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	Green Label Plus 1098
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
WEIGHT DENSITY	101,429
RECYCLED CONTENT	39%
TUFTED WEIGHT	15 oz. per sq. yd. (509 g/m2)
WARRANTIES	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty, 10 Year Limited Colorfastness to Atmospheric Contaminants