

# QUIET THOUGHTS TILE QA120

## PRODUCT SPECIFICATIONS

|                          |                                                                                                                                                                                                                                                                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| STYLE NAME / NUMBER      | Quiet Thoughts Tile / QA120                                                                                                                                                                                                                                                                                                          |
| PRODUCT TYPE             | Carpet Tile                                                                                                                                                                                                                                                                                                                          |
| COLLECTION NAME          | Cognitive                                                                                                                                                                                                                                                                                                                            |
| FIBER TYPE               | Colorstrand SD Nylon                                                                                                                                                                                                                                                                                                                 |
| BACKING                  | UltraSet                                                                                                                                                                                                                                                                                                                             |
| CONSTRUCTION             | Tufted                                                                                                                                                                                                                                                                                                                               |
| SURFACE APPEARANCE       | Patterned Loop                                                                                                                                                                                                                                                                                                                       |
| DYE METHOD               | Solution Dyed                                                                                                                                                                                                                                                                                                                        |
| INSTALLATION METHODS     | Monolithic, QuarterTurn, VerticalAshlar, BrickAshlar, MultiDirectional                                                                                                                                                                                                                                                               |
| SIZE                     | 24" x 24" (.6096 m x .6096 m)                                                                                                                                                                                                                                                                                                        |
| THICKNESS                | .072" (1.82 mm)                                                                                                                                                                                                                                                                                                                      |
| GAUGE                    | 1/12 (47.00 rows per 10 cm)                                                                                                                                                                                                                                                                                                          |
| STITCHES PER INCH        | 12.9 (50.79 per 10 cm)                                                                                                                                                                                                                                                                                                               |
| STAIN RELEASE TECHNOLOGY | Mohawk Protection Plus Stain                                                                                                                                                                                                                                                                                                         |
| DENSITY                  | 8,000                                                                                                                                                                                                                                                                                                                                |
| FLAMMABILITY             | ASTM E 648 Class I (Glue Down)                                                                                                                                                                                                                                                                                                       |
| SMOKE DENSITY            | ASTM E 662 Less than 450                                                                                                                                                                                                                                                                                                             |
| STATIC PROPENSITY        | AATCC-134 Under 3.5 KV                                                                                                                                                                                                                                                                                                               |
| IAQ GREEN LABEL PLUS     | Green Label Plus 1098                                                                                                                                                                                                                                                                                                                |
| SOIL RELEASE TECHNOLOGY  | Mohawk Protection Plus Soil                                                                                                                                                                                                                                                                                                          |
| WEIGHT DENSITY           | 128,000                                                                                                                                                                                                                                                                                                                              |
| RECYCLED CONTENT         | 39%                                                                                                                                                                                                                                                                                                                                  |
| TUFTED WEIGHT            | 16 oz. per sq. yd. (542 g/m <sup>2</sup> )                                                                                                                                                                                                                                                                                           |
| WARRANTIES               | Lifetime Limited Wear Warranty<br>Lifetime Limited Static Protection Warranty<br>Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty<br>Lifetime Limited Colorfastness to Light Warranty<br>10 Year Limited Stain Resistance Warranty, 10 Year Limited Colorfastness to Atmospheric Contaminants |