

IMPLORE TILE QA128

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Implore Tile / QA128
PRODUCT TYPE	Carpet Tile
COLLECTION NAME	Define Tile
FIBER TYPE	Colorstrand Nylon
BACKING	UltraSet
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Textured Loop
DYE METHOD	Solution Dyed/Yarn Dyed
INSTALLATION METHODS	Monolithic, QuarterTurn, MultiDirectional
SIZE	24" x 24" (.6096 m x .6096 m)
THICKNESS	.087" (2.21 mm)
GAUGE	1/12 (47.00 rows per 10 cm)
STITCHES PER INCH	11.4 (44.88 per 10 cm)
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
DENSITY	7,448
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	Green Label Plus 1098
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
WEIGHT DENSITY	134,068
TUFTED WEIGHT	18 oz. per sq. yd. (610 g/m2)
WARRANTIES	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty 10 Year Limited Stain Resistance Warranty (Food & Beverage)