

COMPEL TILE QA129

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Compel Tile / QA129
PRODUCT TYPE	Carpet Tile
COLLECTION NAME	Define Tile
FIBER TYPE	Colorstrand SD Nylon
BACKING	UltraSet
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Textured Loop
DYE METHOD	Solution Dyed
INSTALLATION METHODS	Monolithic, QuarterTurn, MultiDirectional
SIZE	24" x 24" (.6096 m x .6096 m)
THICKNESS	.097" (2.46 mm)
GAUGE	1/12 (47.00 rows per 10 cm)
STITCHES PER INCH	11.8 (46.45 per 10 cm)
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
DENSITY	6,680
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	Green Label Plus 1098
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
WEIGHT DENSITY	147,681
TUFTED WEIGHT	18 oz. per sq. yd. (610 g/m ²)
WARRANTIES	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty 10 Year Limited Stain Resistance Warranty