

WALK THE WALK TILE QA68

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Walk The Walk Tile / QA68
PRODUCT TYPE	Carpet Tile
FIBER TYPE	Colorstrand SD Nylon
BACKING	Ultraset NXT
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Textured Loop
DYE METHOD	Solution Dyed
INSTALLATION METHODS	QuarterTurn, Monolithic, BrickAshlar, VerticalAshlar, MultiDirectional
SIZE	24" x 24" (.6096 m x .6096 m)
THICKNESS	.203" (5.16 mm)
GAUGE	5/32 (25.2 rows per 10 cm)
STITCHES PER INCH	8.5 (33.43 per 10 cm)
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
DENSITY	6,739
FLAMMABILITY	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	Green Label Plus 1171
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
WEIGHT DENSITY	256,082
RECYCLED CONTENT	39%
TUFTED WEIGHT	38 oz. per sq. yd. (1288 g/m2)
WARRANTIES	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty, 10 Year Limited Colorfastness to Atmospheric Contaminants