

SPEED . POWER . VERSATILITY

- 420 IN-LBS OF DRIVING FORCE
- HIGH SPEED OPERATION, 15 SHOTS/SECOND
- SHOOTS BOTH FLAT & CONICAL COILS
- OPTIONAL METAL BELT HOOK AVAILABLE

ADJUSTABLE EXHAUST
ensures workplace comfort

FIRE MODE SWITCH
Switchable between contact fire
and sequential fire modes

TOOL-FREE DEPTH ADJUST

SERRATED CONTACT TIP
DUST COVER



CUSHIONED RUBBER GRIP
ERGONOMIC FRAME
provides comfort and balance

ROBUST CONICAL NYLON
MAGAZINE
industry leading durability

SHOOTS BOTH 6.8 & 8mm PITCH NAILS

NO-MAR PAD INCLUDED

FASTENER SPECIFICATION

Collation:	15° Wire/Plastic Collated
Fastener Lengths:	25~50mm (1"~2")
Shank Dia.:	2.1~2.5mm (.083"~.099")
Head Dia.:	5.2~5.6mm (.202"~.220")
Shank Type:	Smooth, Screw, Ring
Load Capacity:	400 (wire welded) 200 (plastic collated)

TOOL SPECIFICATION

Weight:	4.4 lbs (2.0kg)
Height:	10.6" (271mm)
Width:	4.9" (126mm)
Length:	9.6" (246mm)
Operating Pressure:	70 to 120 PSI (5-8 bars)
Driving Power:	420 in-lbs
Firing mode:	Switchable Trigger
Applications:	Sheathing, Furring, Siding Wooden Fencing, Subfloors

