



# OAK TVETA


The rich, coffee stain on this single-strip oak floor from the Småland Collection allows the fully smoked, charcoal nuances in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

| PRODUCT DETAILS    |                                                                                                                                                                                                                                  | FACTS                |                     | TECHNICAL PROPERTIES                  |             |             |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------------|---------------------------------------|-------------|-------------|
| Article Number     | 151NDSEK04KW240                                                                                                                                                                                                                  | Wood Species         | Oak                 | Moisture content                      | EN13183     | 7%±2%       |
| EAN Code           | 7393969039055                                                                                                                                                                                                                    | Design               | 1-strip             | Minimum Mean Density kg/m³ >500 kg/m³ |             |             |
| Surface treatment  | Oil<br>This floor should be oiled immediately after installation.                                                                                                                                                                | Grading              | Expressive          |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Range                | Kährs Supreme       | Reaction To Fire                      | EN13501-1   | Dfl-s1      |
|                    |                                                                                                                                                                                                                                  | Collection           | Småland Collection  | Formaldehyde Emission                 | EN717-1     | E1          |
| Design features    | Bevelled 4-sided, Brushed, Light smoked, Handscraped, Saw marks                                                                                                                                                                  | Resandable           | 2-4 times           | Content PCP                           | CEN/TR14823 | ≤ 5 x 10-6n |
| Dimensions         | 187 x 2420 mm                                                                                                                                                                                                                    | Natural/Stained      | Stained             | Breaking Strength N/mm²               | EN1533      | NPD         |
|                    |                                                                                                                                                                                                                                  | Brinell Value        | 3,7                 | Thermal Conductivity                  | EN12664     | 0,14 W/mK   |
| Weight per Package | 22 kg                                                                                                                                                                                                                            | Joint                | Woodloc® 5S         | Thermal Resistance R-Value            | .11 (m2K/W) |             |
| Area per Package   | 2.7 m²                                                                                                                                                                                                                           | Floor heating        | Yes                 | Biological Durability                 | EN350-2     | Class 1     |
| Area per pallet    | 122.4 m²                                                                                                                                                                                                                         | Warranty             | 30 years            | CARB2                                 | Compliant   |             |
| Package info       | Packages may contain start and stop boards.                                                                                                                                                                                      | Wear-layer material  | Hardwood            | Slipperiness                          | CEN/TS15676 | NPD         |
| DETAIL DESCRIPTION | All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | Wear Layer Thickness | 3.5 mm              |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Core material        | Pine/Spruce lamella |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Backside material    | Veneer              |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Thickness            | 15 mm               |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Installation method  | Floating, Glue-down |                                       |             |             |
|                    |                                                                                                                                                                                                                                  | Surface Colour       | Shadow Brown        |                                       |             |             |


## COLOUR CHANGE

Stained product - noticeable color change over time.


## Other products in this collection



Oak Klinta




Oak Sevede




Oak Ydre




Oak Möre




Oak Vista



Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeland

## CERTIFICATES



## Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*