



FADED BLACK NARROW

A faded black with the warmth of the oak shining through. Faded black narrow is a single-strip stained sleek oak floor from the Life Collection. A calm wood collection with few knots and an authentic look and feel. Four-sided microbeveling at the edges ensures a classic plank look. The innovative matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | LTCLR3008-118 |
| EAN Code | 7393969107587 |
| Surface treatment | Matt lacquer |
| Design features | Microbevelled 4-sided |
| Dimensions | 118 x 1225 mm |
| Weight per Package | 10.9 kg |
| Area per Package | 1.74 m ² |
| Area per pallet | 104.4 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|----------------------------------|----------------------------|
| Wood Species | Oak |
| Design | 1-strip |
| Grading | Calm |
| Range | Kährs Life |
| Collection | Life Collection |
| Resandable | Not resandable |
| Natural/Stained | Stained |
| Joint | Woodloc® 5G |
| Floor heating | Yes |
| Warranty | 15 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 0.6 mm |
| Core material | HDF |
| Thickness | 7 mm |
| Installation method | Glue-down, Floating |
| Resistance to indentation | >40 Newton/mm ² |


TECHNICAL PROPERTIES

| | | |
|--|----------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >800 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Cfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,134 W/mK |
| Thermal Resistance R-Value | .0533 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Resistance to indentation | >40 Newton/mm ² | |

Other products in this collection



Cocoa Bean 2-strip



Pure Walnut 2-strip



Faded Black 2-strip



Butterscotch 2-strip



Earl Grey 2-strip



Driftwood 2-strip



Whole Grain 2-strip



Pure Oak 2-strip



Light Suede 2-strip



Coconut Cream 2-strip



Cocoa Bean Narrow



Pure Walnut Narrow



Faded Black Narrow



Butterscotch Narrow



Earl Grey Narrow



Driftwood Narrow



Whole Grain Narrow



Pure Oak Narrow



Light Suede Narrow



Coconut Cream Narrow



Cocoa Bean Wide



Pure Walnut Wide



Faded Black Wide



Butterscotch Wide



Earl Grey Wide



Driftwood Wide



Whole Grain Wide



Pure Oak Wide



Coconut Cream Wide

Light Suede Wide

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.