



## OAK VISTA

This misty white stained, single-strip oak floor from the Småland Collection gracefully balances the light and dark contrasts in the wood. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

### PRODUCT DETAILS

|                    |   |
|--------------------|---|
| Article Number     | 151NCSEK02KW240   |
| EAN Code           | 7393969038973   |
| Surface treatment  | Oil<br>This floor should be oiled immediately after installation. |
| Design features    | Bevelled 4-sided, Brushed, Handscraped                            |
| Dimensions         | 187 x 2420 mm   |
| Weight per Package | 22 kg   |
| Area per Package   | 2.7 m <sup>2</sup>  |
| Area per pallet    | 122.4 m <sup>2</sup>  |
| Package info       | Packages may contain start and stop boards.                       |

### FACTS

|                      |                    |
|----------------------|--------------------|
| Range                | Kährs Original     |
| Collection           | Småland Collection |
| Wear Layer Thickness | 3.5 mm             |
| Thickness            | 15 mm              |

### TECHNICAL PROPERTIES

|  |                        |                          |
|--|------------------------|--------------------------|
| Moisture content                       | EN13183                | 7%±2%                    |
| Minimum Mean Density kg/m <sup>3</sup> | >500 kg/m <sup>3</sup> |                          |
| Reaction To Fire                       | EN13501-1              | Dfl-s1                   |
| Formaldehyde Emission                  | EN717-1                | E1                       |
| Content PCP                            | CEN/TR14823            | ≤ 5 x 10 <sup>-6</sup> n |
| Breaking Strength N/mm <sup>2</sup>    | EN1533                 | NPD                      |
| Thermal Conductivity                   | EN12664                | 0,14 W/mK                |
| Thermal Resistance R-Value             | .11 (m2K/W)            |                          |
| Biological Durability                  | EN350-2                | Class 1                  |
| CARB2                                  | Compliant              |                          |
| Slipperiness                           | CEN/TS15676            | NPD                      |

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

Other products in this collection



Oak Klinta



Oak Sevede



Oak Ydre



Oak Möre



Oak Vista



Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeland

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.