



# OAK MUSE

The muted grey-brown tones in this single-strip oak floor from the Canvas Collection, are enhanced by an even stain, resulting in a timeless expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

| PRODUCT DETAILS                                     |                                             | FACTS                |                     | TECHNICAL PROPERTIES       |             |             |
|-----------------------------------------------------|---------------------------------------------|----------------------|---------------------|----------------------------|-------------|-------------|
| Article Number                                      | 13103AEK1VKW185                             | Wood Species         | Oak                 | Moisture content           | EN13183     | 7%±2%       |
| EAN Code                                            | 7393969043120                               | Design               | 1-strip             | Minimum Mean Density kg/m³ |             |             |
| Surface treatment                                   | Matt lacquer                                | Grading              | Variation           | >500 kg/m³                 |             |             |
| Design features                                     | Microbevelled 4-sided, Brushed              | Range                | Kährs Avanti        | Reaction To Fire           | EN13501-1   | Dfl-s1      |
| Dimensions                                          | 127 x 1860 mm                               | Collection           | Canvas Collection   | Formaldehyde Emission      | EN717-1     | E1          |
| Weight per Package                                  | 12.687 kg                                   | Resandable           | 2-3 times           | Content PCP                | CEN/TR14823 | ≤ 5 x 10-6n |
| Area per Package                                    | 1.652 m²                                    | Natural/Stained      | Stained             | Breaking Strength N/mm²    | EN1533      | NPD         |
| Area per pallet                                     | 104.076 m²                                  | Brinell Value        | 3,7                 | Thermal Conductivity       | EN12664     | 0,08 W/mK   |
| Package info                                        | Packages may contain start and stop boards. | Joint                | Woodloc®            | Thermal Resistance R-Value |             | .15 (m2K/W) |
| DETAIL DESCRIPTION                                  |                                             | Floor heating        | Yes                 | Biological Durability      | EN350-2     | Class 1     |
|                                                     |                                             | Warranty             | 25 years            | CARB2                      |             | Compliant   |
|                                                     |                                             | Warranty US          | 25 years            | Slipperiness               | CEN/TS15676 | NPD         |
|                                                     |                                             | Wear-layer material  | Hardwood            |                            |             |             |
| COLOUR CHANGE                                       |                                             | Wear Layer Thickness | 3 mm                |                            |             |             |
|                                                     |                                             | Core material        | Pine/Spruce lamella |                            |             |             |
|                                                     |                                             | Thickness            | 13 mm               |                            |             |             |
| Stained product - noticable color change over time. |                                             | Installation method  | Floating, Glue-down |                            |             |             |

Other products in this collection



Oak Fawn



Oak Henna



Oak Heather



Oak Cadence



Oak Reiter



Oak Muse



Oak Curio



Oak Carbon



Oak Etch



Oak Tuft



Oak Mostra

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*