

Monroe 1609

Engineered Hardwood • Casting

Benefits

- Quickship
- Performant and durable construction
- Easy and versatile Installation
- Safe and healthy
- Environmentally-Friendly
- Notable look



Product Specifications

Brand	UrbanTerra
Collection	Casting
Style Name	Monroe
Style Number	1609
Construction	Engineered Hardwood
Format	Plank
Species	European White Oak
Core	Eucalyptus
Grade	Classic
Wood Veneer Thickness	0.079" (2 mm)
Wood Veneer	Sliced
Total Thickness	0.472" (12 mm)
Width	7,48" (190 mm)
Length(s)	Random (Variées)
Edges	4-Sided Micro Bevel
Locking System	Tongue & Groove
Finish	Lightly Wire-Brushed
Top Surface	UV-Cured Urethane
Gloss	Mat
Abrasion Resistance	Residential Use
Formaldehyde	n/a
Certifications	BLC Certification, FloorScore, Quickship
Installation Method	Floating, Glued, Nail, Compatible With Embedded Radiant Heating, Staple
Residential Warranty	Structural Integrity <i>Lifetime</i> Finish <i>35 Years</i> No Questions Asked Replacement <i>Minimum 30 Days</i>

Packaging Information

Planks Per Box	8
Boxes Per Pallet	45
Box Weight	54.07 Pounds (24529.92 Grams)
Square Feet Per Box	31.08
Square Meters Per Box	2.89
Square Feet Per Pallet	1398.87
Square Meters Per Pallet	129.96

Moldings



Flushmount Reducer
Coordinating
92" X 0.472" X 2"
(2336 mm X 12 mm X 51 mm)



Flushmount Stair Nose
Coordinating
92" X 0.472" X 3.110"
(2336 mm X 12 mm X 79 mm)



Square Nose
Coordinating
92" X 0.472" X 2"
(2336 mm X 12 mm X 50.80 mm)



T-Molding
Coordinating
92" X 0.472" X 2"
(2336 mm X 12 mm X 51 mm)