

# Pebble Creek 2263

## Engineered Luxury Vinyl - SPC • Therma Nature

### Benefits

- Family friendly (including pet)
- Safe and healthy
- Easy maintenance
- Quiet and comfortable
- Notable look
- Performant and durable construction
- Easy and versatile Installation
- Best-in-class Warranty



### Product Specifications

|                             |  |
|-----------------------------|--|
| <b>Brand</b>                | HydraLuxe Rigid  |
| <b>Collection</b>           | Therma Nature  |
| <b>Style Name</b>           | Pebble Creek   |
| <b>Style Number</b>         | 2263   |
| <b>Construction</b>         | Engineered Luxury Vinyl  |
| <b>Sub Category</b>         | SPC  |
| <b>Format</b>               | Plank  |
| <b>Material</b>             | Virgin PVC   |
| <b>Core Material</b>        | 70% Calcium Carbonate / 30% Vinyl  |
| <b>Backing</b>              | Cork   |
| <b>Design</b>               | Wood   |
| <b>Wear Layer Thickness</b> | 0.02" (0.5 mm)   |
| <b>Vinyl Thickness</b>      | n/a  |
| <b>Core Thickness</b>       | 0.157" (4 mm)  |
| <b>Backing Thickness</b>    | 0.0394" (1 mm)   |
| <b>Total Thickness</b>      | 0.197" (5 mm)  |
| <b>Width</b>                | 7.087" (180 mm)  |
| <b>Length(s)</b>            | 48.031" (1220 mm)  |
| <b>Edges</b>                | 4-Sided Macro Painted Bevel  |
| <b>Locking System</b>       | Välinge 5Gi  |
| <b>Finish</b>               | Medium Embossed  |
| <b>Top Surface</b>          | UV-Cured Polyurethane & Ceramic Bead Technology  |
| <b>Abrasion Resistance</b>  | General Commercial Use   |
| <b>Gloss</b>                | Mat  |
| <b>IIC</b>                  | 72   |
| <b>STC</b>                  | 73   |
| <b>Formaldehyde</b>         | E1   |
| <b>Pattern Repeat</b>       | 5  |
| <b>Certifications</b>       | BLC Certification, Designers' Choice, Phthalates Free, E1 Certified, FloorScore, GreenGuard Gold Certified   |
| <b>Installation Method</b>  | Floating, Compatible With Embedded Radiant Heating   |
| <b>Residential Warranty</b> | Manufacturing Defects <i>Lifetime</i><br>Wear <i>Lifetime</i><br>Stain Resistance <i>Lifetime</i><br>Fade <i>Lifetime</i><br>No Questions Asked Replacement <i>Minimum 30 Days</i><br>Waterproof <i>Lifetime</i><br>Petproof <i>Lifetime</i> |
| <b>Commercial Warranty</b>  | Manufacturing Defects <i>15 Years</i><br>Wear <i>15 Years</i><br>Stain Resistance <i>15 Years</i><br>Fade <i>15 Years</i><br>Waterproof <i>Lifetime</i><br>Petproof <i>Lifetime</i>  |

### Packaging Information

|                                 |                               |
|---------------------------------|-------------------------------|
| <b>Planks Per Box</b>           | 8                             |
| <b>Boxes Per Pallet</b>         | 70                            |
| <b>Box Weight</b>               | 33.09 Pounds (15010.51 Grams) |
| <b>Square Feet Per Box</b>      | 18.91                         |
| <b>Square Meters Per Box</b>    | 1.76                          |
| <b>Square Feet Per Pallet</b>   | 1323.7                        |
| <b>Square Meters Per Pallet</b> | 122.98                        |

### Moldings

**Flushmount Stair Nose Matching**  
94.488" X .984" X 2.834"  
(2400 mm X 25 mm X 72 mm)

**Reducer Matching**  
94.488" X 0.281" X 1.771"  
(2400 mm X 7 mm X 45 mm)

**T-Molding Matching**  
94.488" X 0.315" X 1.771"  
(2400 mm X 8 mm X 45 mm)