

## Waterproofing Kits

### Item Code and Description

- a. WP1000-PRE . . . Premium Kit
- b. WP1090-PRO . . . Pro Kit

### **General Product Description**

- a. pre-assembled kits for waterproofing showers constructed with ARC shower bases
- b. select a kit based on installer's needs and preferences
- c. additional waterproofing supplies may be needed depending on the area of coverage, number of joints and supply lines, number of corners and types of corners, benches, niches, overall square footage of project, etc.
- d. consult the Specification Sheet for each a la carte waterproofing item for specific product details

### Premium Kit

- a. sufficient waterproofing supplies for a typical alcove (three-walled) shower installation using an ARC base, including the shower base and walls, plus additional supplies for installing the base and applying the waterproofing materials
- b. additional waterproofing supplies may be needed depending on project requirements
- c. follow ARC's installation instructions to waterproof the shower base and walls properly
- d. kit includes:
  - 1. 2 gallons of TANK/10 waterproofing compound (covers approximately 120 sq. ft. with two coats)
  - 2. 75 ft. of joint reinforcement tape (3 25 ft. rolls)
  - 3. 4 internal corners
  - 4. 1 supply gasket
  - 5. 25 #9 x 2½" Torx weatherproof screws
  - 6. 1 Torx power bit driver
  - 7. 6 10 oz. tubes of Tank/10 polyurethane construction adhesive
  - 8. 1 10 oz. tube of painter's acrylic caulk (brand may vary)
  - 9. 1 paint roller handle
  - 10. 2 paint roller covers
  - 11. 1 paint brush
- 12. 2 pairs of nitrile gloves, size large Painter's acrylic Waterproofing **Polyurethane** caulk compound construction Premium Kit adhesive Joint reinforcement tape Internal corners Mixer valve gasket Paint roller Nitrile gloves handle **Paint** roller Supply gasket covers Paint brush Torx screws and driver



# Waterproofing Kits

#### Pro Kit

- a. sufficient waterproofing supplies for covering an ARC shower base only, , plus additional supplies for installing the base and applying the waterproofing materials
- b. installers choose this kit when they prefer to use a different waterproofing product on the walls and surrounding floor, most typically uncoupling underlayment
- c. Tank/10 waterproofing compound is typically used to overlap any other waterproofing materials used on the walls and/or surrounding floor
- d. additional waterproofing supplies may be needed depending on project requirements
- e. follow ARC's installation instructions to waterproof the shower base properly
- f. kit includes:
  - 1. 1 gallon of TANK/10 waterproofing compound (covers approximately 60 sq. ft. with two coats)
  - 2. 25 ft. of joint reinforcement tape
  - 3. 2 internal corners
  - 4. 25 #9 x 2" Torx weatherproof screws
  - 5. 1 Torx power bit driver
  - 6. 6 10 oz. tubes of Tank/10 polyurethane construction adhesive
  - 7. 1 10 oz. tube of painter's acrylic caulk (brand may vary)
  - 8. 1 paint roller handle
  - 9. 2 paint roller covers
  - 10. 1 paint brush

Nitrile glove:

11. 2 — pairs of nitrile gloves, size large



Torx screws and driver

Pro Kit

Paint brush

Internal corners