

**SCS Global Services** does hereby certify that an independent assessment has been conducted on behalf of:

# Uzin Utz North America, Inc.

14509 E. 33rd Place, Unit G, Aurora, CO, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

## Indoor Advantage™ Gold

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method (CA 01350) v1.2-2017 (effective January 2017) for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, SCAQMD Rule 1113 - Architectural Coatings (September 2013); European Decopaint (2004/42/EC); Canadian VOC Concentration Limits for Architectural Coatings (SOR/2009-264: April 16, 2014); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 136 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 mg.m<sup>3</sup> and 5.0 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-IAQ-08157

Valid from: August 11, 2022 to August 10, 2023



INDOOR ADVANTAGE GOLD  
BUILDING MATERIALS



A handwritten signature in black ink that reads "Stanley Mathuram".

Stanley Mathuram, PE, Executive Vice President  
SCS Global Services  
2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

## Certification Addendum

# Uzin Utz North America, Inc.

Certification: Registration # SCS-IAQ-08157 | Valid from: August 11, 2022 to August 10, 2023

### Indoor Advantage™ Gold

Addendum Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conformance: Conforms to the CDPH/EHLB Standard Method (CA 01350) v1.2-2017 (effective January 2017) for the school classroom, private office, and single-family residence parameters when modeled as Flooring. Also, SCAQMD Rule 1113 - Architectural Coatings (September 2013); European Decopaint (2004/42/EC); Canadian VOC Concentration Limits for Architectural Coatings (SOR/2009-264: April 16, 2014); Hong Kong Air Pollution Control (VOC) Regulation.

Standard Product Application Amount: 136 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 mg/m<sup>3</sup> and 5.0 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.2-2017)

### Products: Coatings:

Pallman PALL-X-2 Kolorit *(Added: February 7, 2023)*, Pallmann Magic Oil 2k, Pallmann P104 Turbo, Pallmann P108 Defend, Pallmann PALL-X 96 NEXGEN, Pallmann PALL-X Bond, Pallmann PALL-X Clear, Pallmann PALL-X Color, Pallmann PALL-X Gold, Pallmann PALL-X Natureseal, Pallmann PALL-X POWER, Pallmann PALL-X Pure, Pallmann PALL-X Whiteseal, UZIN NC 110, UZIN NC 144 LW UZIN NC 147, UZIN NC 150, UZIN NC 157, UZIN NC 170, UZIN NC 172 BiTurbo, UZIN NC 182 MT, UZIN NC 886, UZIN NC 888, UZIN NC 890, UZIN PE 260, UZIN PE 280, UZIN PE 360 Plus, UZIN PE 414 Turbo, UZIN PE 460