

Mapefloor Filler

Microcrystalline, Anti-Slip Additive

DESCRIPTION

Mapefloor™ Filler is a dry powder additive that is easily dispersed into select resinous flooring products and coatings to improve slip resistance of the resulting finish.

FEATURES AND BENEFITS

- Enhances traction on steps, floors, decks, ramps, etc.
- To replace the silica aggregate used to create a textured finish
- Provides a uniform distribution of texture

WHERE TO USE

- For use with select MAPEI resinous flooring finishes and coatings, such as *Mapefloor Finish 58 W* and *Mapecoat™ Deck S*

MIXING

Before product use, take appropriate safety precautions. Refer to the Safety Data Sheet for details.

1. Contents of the *Mapefloor Filler* container should be free-flowing and void of any clumps.
2. Slowly add *Mapefloor Filler* to the coating while mixing.
3. To ensure that all solids are evenly dispersed, mix *Mapefloor Filler* mechanically for about 1 minute after adding into the finish or coating. Use an adequate mixing paddle with a low-speed drill mixer (at 300 to 400 rpm).

PRODUCT APPLICATION

- *Mapefloor Filler* is used as an additive in a topcoat for resinous flooring finishes and coatings. Add up to 5% by weight of *Mapefloor Filler*, referring to individual Technical Data Sheets for additional instructions and application rates.
- Mockups are recommended to determine the topcoat selection and application rates required to produce the desired texture.

Consult MAPEI's Technical Services Department for installation recommendations regarding substrates and conditions not listed.

CLEANUP

- Clean all tools and equipment with a suitable solvent. Hardened or cured material must be mechanically removed.

LIMITATIONS

- The addition of *Mapefloor Filler* will reduce the gloss level of the finished flooring system.
- The resulting texture of *Mapefloor Filler* will reduce the dirt pick-up resistance and cleanability of the surface.

Shelf Life and Product Characteristics

before mixing

Storage	Shelf life is 1 year if product is stored in its original, unopened packaging in a dry area at 41°F to 95°F (5°C to 35°C)
Physical state	Powder
Color	White
Density	1.6 U.S. oz./inch ³ (2.70 g/mL)

Packaging

Size

Bucket: 0.66 lbs. (0.30 kg)

ADDITIONAL INFORMATION

Refer to the SDS for specific data related to health and safety as well as product handling.

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:

Flooring: 1-800-992-6273

Concrete and heavy construction: 1-888-365-0614

Canada:

1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: June 13, 2023 MK 00166 (23-2019)

For the most current product data and BEST-BACKEDSM warranty information,
visit www.mapei.com.

All Rights Reserved. © 2023 MAPEI Corporation.

