

Safety Data Sheet

MAPEFLEX P2 SL PART A

Safety Data Sheet dated: 02/25/2023 - version 7

Date of first edition: 03/08/2017



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: MAPEFLEX P2 SL PART A

Trade code: 9019101

Recommended use of the chemical and restrictions on use

Recommended use: Polyurethane-based adhesive

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION



Classification of the chemical

Flammable Liquids — Category 3

Eye irritation, Category 2A

Skin Sensitization, Category 1

Flammable liquid and vapour.

Causes serious eye irritation.

May cause an allergic skin reaction.

Label elements

Hazard pictograms and Signal Word



Warning

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Concentration (%) w/w	Name	Ident. Numb.	Classification	Registration Number
2.5-5 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	
2.5-5 %	calcium oxide; quicklime	CAS:1305-78-8 EC:215-138-9	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Dam. 1, H318	
1-2.5 %	xylenes; 1,2 dimethylbenzene	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315	
0.49-1 %	ethyl benzene; aethylbenzol	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; Asp. Tox. 1, H304	
0.1-0.25 %	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	CAS:41556-26-7 EC:255-437-1	Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available

Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

List of components with OEL value

	OEL Type	Country	Occupational Exposure Limit	
titanium dioxide; Dioxotitanium CAS: 13463-67-7	OSHA		Long Term 15 mg/m ³	
	ACGIH		Long Term 10 mg/m ³ A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation;	
	MAK	GERMANY	Long Term 0.3 mg/m ³	
	ACGIH		Long Term 10 mg/m ³ A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation	
	MAK	AUSTRIA	Long Term 5 mg/m ³ ; Short Term 10 mg/m ³	
	MAK	SWITZERLAND	Long Term 3 mg/m ³	
calcium oxide; quicklime CAS: 1305-78-8	OSHA		Long Term 5 mg/m ³	
	ACGIH		Long Term 2 mg/m ³ upper respiratory tract irritation;	
	MAK	GERMANY	Long Term 1 mg/m ³	
	ACGIH		Long Term 2 mg/m ³ upper respiratory tract irritation	
	MAK	AUSTRIA	Long Term 1 mg/m ³ ; Short Term 4 mg/m ³	
	MAK	SWITZERLAND	Long Term 2 mg/m ³	
xylenes; 1,2 dimethylbenzene CAS: 1330-20-7	OSHA		Long Term 435 mg/m ³ - 100 ppm	
	ACGIH		Long Term 100 ppm; Short Term 150 ppm A4 - Not Classifiable as a Human Carcinogen;CNS impairment;eye and upper respiratory tract irritation;	
	EU		Long Term 221 mg/m ³ - 50 ppm; Short Term 442 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin;	
	MAK	GERMANY	Long Term 220 mg/m ³ - 50 ppm	
	ACGIH		Long Term 100 ppm; Short Term 150 ppm A4 - Not Classifiable as a Human Carcinogen;CNS impairment;eye and upper respiratory tract irritation	
	MAK	AUSTRIA	Long Term 221 mg/m ³ - 50 ppm; Short Term 442 mg/m ³ - 100 ppm	
	MAK	SWITZERLAND	Long Term 435 mg/m ³ - 100 ppm	
	EU		Long Term 221 mg/m ³ - 50 ppm; Short Term 442 mg/m ³ - 100 ppm Behaviour Indicative Possibility of significant uptake through the skin (pure)	
	ethyl benzene; aethylbenzol CAS: 100-41-4	OSHA		Long Term 435 mg/m ³ - 100 ppm
		ACGIH		Long Term 20 ppm

		A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment;
EU		Long Term 442 mg/m ³ - 100 ppm; Short Term 884 mg/m ³ - 200 ppm Behaviour Indicative Possibility of significant uptake through the skin;
MAK	GERMANY	Long Term 88 mg/m ³ - 20 ppm
ACGIH		Long Term 20 ppm A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
MAK	AUSTRIA	Long Term 440 mg/m ³ - 100 ppm; Short Term 880 mg/m ³ - 200 ppm
MAK	SWITZERLAND	Long Term 220 mg/m ³ - 50 ppm
	D	
EU		Long Term 442 mg/m ³ - 100 ppm; Short Term 884 mg/m ³ - 200 ppm Behaviour Indicative Possibility of significant uptake through the skin

Biological Exposure Index

xylenes; 1,2
dimethylbenzene
CAS: 1330-20-7

Biological Indicator: Methyl uric Acid; Sampling Period: End of turn
Value: 1.5 GGCREAT; Medium: Urine

ethyl benzene;
aethylbenzol
CAS: 100-41-4

Biological Indicator: Mandelic acid and fenilgliossalico; Sampling Period: End of turn; End of working week
Value: 0.7 GGCREAT; Medium: Urine
Remark: Not Specific; Semiquantitative

Biological Indicator: Ethylbenzene; Sampling Period: Not critical
Medium: Air at the end of exhalation
Remark: Semiquantitative

Biological Indicator: Mandelic acid and fenilgliossalico; Sampling Period: End of turn
Value: 0.15 GGCREAT; Medium: Urine
Remark: Not Specific

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste Grey

Odour: Like: Xylene

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 56.2 °C (133.2 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: No data available

Relative density: 1.70 g/cm³

Solubility in water: No data available
Solubility in oil: No data available
Partition coefficient (n-octanol/water): No data available
Auto-ignition temperature: No data available
Decomposition temperature: No data available
Viscosity: No data available
Explosive properties: No data available
Oxidizing properties: No data available
Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available
Miscibility: No data available
Fat Solubility: No data available
Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

titanium dioxide;
Dioxotitanium

a) acute toxicity	LD50 Oral Rat > 10000 mg/kg
-------------------	-----------------------------

calcium oxide; quicklime

a) acute toxicity	LD50 Oral Rat = 500 mg/kg
-------------------	---------------------------

xylenes; 1,2

a) acute toxicity	LC50 Inhalation Rat = 47635 mg/l 4h
-------------------	-------------------------------------

dimethylbenzene

LD50 Oral Rat = 4300 mg/kg
LD50 Skin Rabbit > 4350 mg/kg
LC50 Inhalation Rat = 29.08 mg/l 4h
LD50 Oral Rat = 3500 mg/kg

ethyl benzene;
aethylbenzol

a) acute toxicity

LD50 Skin Rabbit = 15354 mg/kg

LC50 Inhalation Rat = 172 mg/l 4h
LD50 Oral Rat = 3500 mg/kg
LD50 Skin Rabbit = 15400 mg/kg
LC50 Inhalation Rat = 17.4 mg/l 4h
LD50 Oral Rat = 3500 mg/kg

bis(1,2,2,6,6-
pentamethyl-4-piperidyl)
sebacate; Decanedioic
acid, bis(1,2,2,6,6-
pentamethyl-4-
piperidiny) ester

a) acute toxicity

LD50 Oral Rat = 2615 mg/kg

Substance(s) listed on the IARC Monographs:

titanium dioxide; Dioxititanium Group 2B
xylenes; 1,2 dimethylbenzene Group 3
ethyl benzene; aethylbenzol Group 2B

Substance(s) listed as OSHA Carcinogen(s):

titanium dioxide; Dioxititanium
ethyl benzene; aethylbenzol

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; Dioxititanium

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards
Based on available data, the classification criteria are not met

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
calcium oxide; quicklime	CAS: 1305-78-8 - EINECS: 215-138-9	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID
xylenes; 1,2 dimethylbenzene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA
		a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID

ethyl benzene; aethylbenzol CAS: 100-41-4 - EINECS: 202-849-4 - INDEX: 601-023-00-4

a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID
a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA
a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h
a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h
a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 11 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 32 mg/L 96h EPA
a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata > 438 mg/L 96h IUCLID
a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 4.2 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 7.55 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 9.1 mg/L 96h EPA
a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 9.6 mg/L 96h EPA
a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 1.8 mg/L 48h IUCLID
a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 4.6 mg/L 72h IUCLID
a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 2.6 mg/L 72h EPA
a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 1.7 mg/L 96h EPA
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester CAS: 41556-26-7 - EINECS: 255-437-1

a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0.97 mg/L 96h

Persistence and degradability

Not available

Bioaccumulative potential

Not available

Mobility in soil

Not available

Other adverse effects

Not available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN1993
ADR-UN number: 1993
IATA-Un number: 1993
IMDG-Un number: 1993

UN proper shipping name

DOT-Proper Shipping Name: Flammable liquids, n.o.s. (xylene - ethylbenzene)
ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (xylene - ethylbenzene)
IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (xylene - ethylbenzene)
IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (xylene - ethylbenzene)

Transport hazard class(es)

DOT-Hazard Class: 3
ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

Packing group

DOT-Packing group: III
ADR-Packing Group: III
IATA-Packing group: III
IMDG-Packing group: III

Environmental hazards

Marine pollutant: No
Environmental Pollutant: Not Applicable
DOT-RQ: Not Applicable

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): B1, B52, IB3, T4, TP1, TP29
DOT-Label(s): 3
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A
DOT-Passenger Aircraft: N/A
DOT-Bulk: N/A
DOT-Non-Bulk: N/A

Road and Rail (ADR-RID) :

ADR-Label: 3
ADR-Hazard identification number: 30
ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 355
IATA-Cargo Aircraft: 366
IATA-Label: 3
IATA-Subsidiary hazards: -
IATA-Erg: 3L
IATA-Special Provisioning: A3

Sea (IMDG) :

IMDG-Stowage Code: Category A
IMDG-Stowage Note: -
IMDG-Subsidiary hazards: -
IMDG-Special Provisioning: 223 274 955

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

titanium dioxide; Dioxotitanium is listed in TSCA Section 8b
calcium oxide; quicklime is listed in TSCA Section 8b
xylenes; 1,2 dimethylbenzene is listed in TSCA Section 8b
ethyl benzene; aethylbenzol is listed in TSCA Section 8b
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

xylenes; 1,2 dimethylbenzene
ethyl benzene; aethylbenzol

Section 313 - Toxic chemical list:

xylenes; 1,2 dimethylbenzene
ethyl benzene; aethylbenzol

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

xylenes; 1,2 dimethylbenzene	Reportable quantity:	100	pounds
ethyl benzene; aethylbenzol	Reportable quantity:	1000	pounds

CAA - Clean Air Act

CAA listed substances:

xylenes; 1,2 dimethylbenzene is listed in CAA Section 112(b) - HAP Section 112(b) - HON
ethyl benzene; aethylbenzol is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

xylenes; 1,2 dimethylbenzene is listed in CWA Section 311
ethyl benzene; aethylbenzol is listed in CWA Section 307 Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; Dioxotitanium Listed as carcinogen
ethyl benzene; aethylbenzol Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide; Dioxotitanium
calcium oxide; quicklime
xylenes; 1,2 dimethylbenzene
ethyl benzene; aethylbenzol

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

titanium dioxide; Dioxotitanium
calcium oxide; quicklime

xylenes; 1,2 dimethylbenzene
ethyl benzene; aethylbenzol

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

titanium dioxide; Dioxotitanium
calcium oxide; quicklime
xylenes; 1,2 dimethylbenzene
ethyl benzene; aethylbenzol

Canada - Federal regulations

DSL - Domestic Substances List

DSL (Domestic Substances List)

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL (Non Domestic Substances List)

No substances listed

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 2/25/2023 - version 7

Additional classification information

NFPA Health: 1 = Slight
NFPA Flammability: 2 = Combustible liquid
NFPA Reactivity: 0 = Minimal
NFPA Special Risk: Not available



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3

B.6/2	Flam. Liq. 2	Flammable Liquids — Category 2
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
US-HAE/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 IMDG: International Maritime Code for Dangerous Goods.
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 CLP: Classification, Labeling, Packaging.
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 INCI: International Nomenclature of Cosmetic Ingredients.
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 DNEL: Derived No Effect Level.
 PNEC: Predicted No Effect Concentration.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 WGK: German Water Hazard Class.
 KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION