# Safety Data Sheet KERAPOXY / A

Safety Data Sheet dated: 12/14/2023 - version 8

Date of first edition: 05/13/2015



### 1. IDENTIFICATION

### **Product identifier**

Mixture identification:

Trade name: KERAPOXY / A Trade code: 905UC9990

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy grout Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

**Emergency 24 hour numbers:** 

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

# 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Skin irritation, Category 2 Causes skin irritation.

Eye irritation, Category 2A Causes serious eye irritation.

Skin Sensitization, Category 1B May cause an allergic skin reaction.

Acute aquatic hazard, category 3 Harmful to aquatic life

Chronic (long term) aquatic hazard, category 3 Harmful to aquatic life with long lasting effects.

**Label elements** 

### **Hazard pictograms and Signal Word**



# Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 1 of 10

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

### Ingredient(s) with unknown acute toxicity:

None

# Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### **Substances**

Not Relevant

#### **Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

# List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
50-75 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
10-20 %	bis-[4-(2,3- epoxipropoxi)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 Index:603-073- 00-2	H317; Eye İrrit. 2A, H319; Aquatic Chronic 2, H411; Aquatic Acute 2,	
5-10 %	titanium dioxide; Dioxotitanium	CAS:13463-67-7 EC:236-675-5 Index:022-006- 00-2	Carc. 2, H351	
5-10 %	alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	CAS:68609-97-2 EC:271-846-8 Index:603-103- 00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317	01-2119485289-22-XXXX
1-2.5 %	formaldehyde, polymer with 2- (chloromethyl)oxirane and phenol;	CAS:9003-36-5 EC:701-263-0	Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317	01-2119454392-40-XXXX

### 4. FIRST AID MEASURES

# **Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 2 of 10

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

# Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

### Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

### 5. FIRE-FIGHTING MEASURES

### **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

### Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant Oxidizing properties: Not Relevant

### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

# **6. ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

# Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 3 of 10

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OEL

### **Control parameters**

### **Community Occupational Exposure Limits (OEL)**

**Type**silica sand; quartz ACGIH Long Term: 0.025 mg/m3
CAS: 14808-60-7 A2 - Suspected Human Carc

Country

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis;

**Occupational Exposure Limit** 

ACGIH Long Term: 0.025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis

MAK AUSTRIA Long Term: 0.15 mg/m3 MAK SWITZERLAN Long Term: 0.15 mg/m3

D

titanium dioxide; Dioxotitanium CAS: 13463-67-7 OSHA Long Term: 15 mg/m3

ACGIH Long Term: 10 mg/m3

A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation;

MAK GERMANY Long Term: 0.3 mg/m3
ACGIH Long Term: 10 mg/m3

A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation

MAK AUSTRIA Long Term: 5 mg/m3; Short Term: 10 mg/m3

MAK SWITZERLAN Long Term: 3 mg/m3

D

### Predicted No Effect Concentration (PNEC) values

alkyl epoxy resin; Exposure Route: Marine water; PNEC Limit: 0.00072 mg/l

Oxirane, mono((C12-14-alkyloxy)methyl)

derivatives CAS: 68609-97-2

Exposure Route: Fresh Water; PNEC Limit: 0.0072 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 66.77 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 6.677 mg/kg

Exposure Route: Soil; PNEC Limit: 80.12 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

formaldehyde, polymer

with 2-

(chloromethyl)oxirane and phenol; CAS: 9003-36-5

Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.294 mg/kg

Exposure Route: Marine water; PNEC Limit: 0.0003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.0294 mg/kg

Exposure Route: Soil; PNEC Limit: 0.237 mg/kg

Appropriate engineering controls: Not available

### **Individual protection measures**

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 4 of 10

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

# Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: paste white

Odour: characteristic

Odour threshold: Not Relevant

pH: Not Relevant

Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant

Flash point: 100 °C (212 °F) Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant Vapour pressure: Not Relevant Relative density: 1.45 g/cm3 Solubility in water: insoluble Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant Decomposition temperature: Not Relevant

Viscosity: Not Relevant

Explosive properties: Not Relevant Oxidizing properties: Not Relevant Solid/gas flammability: Not Relevant

### Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

### 10. STABILITY AND REACTIVITY

### Reactivity

Stable under normal conditions

# **Chemical stability**

Data not available.

### Possibility of hazardous reactions

None.

# **Conditions to avoid**

Stable under normal conditions.

### **Incompatible materials**

None in particular.

### **Hazardous decomposition products**

None.

# 11. TOXICOLOGICAL INFORMATION

# Information on toxicological effects

# **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met  $% \left( 1\right) =\left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right)$ 

b) skin corrosion/irritation The product is classified: Skin irritation, Category 2(H315) c) serious eye damage/irritation The product is classified: Eye irritation, Category 2A(H319)

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 5 of 10

d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1B(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

### Toxicological information on main components of the mixture:

silica sand; quartz a) acute toxicity LD50 Oral Rat = 500 mg/kg

bis-[4-(2,3-LD50 Skin Rabbit = 20 mg/kg a) acute toxicity

epoxipropoxi)phenyl]

propane

LD50 Oral Rat =  $11300 \mu L/kg$ 

titanium dioxide; a) acute toxicity LD50 Oral Rat > 10000 mg/kg

Dioxotitanium

a) acute toxicity

LD50 Oral Rat = 19200 mg/kg

alkyl epoxy resin; Oxirane, mono((C12-14-

derivatives

alkyloxy)methyl)

LD50 Skin Rabbit = 4000 mg/kg

formaldehyde, polymer a) acute toxicity LD50 Oral Rat > 5000 mg/kg

with 2-

(chloromethyl)oxirane

and phenol;

LD50 Skin Rat > 2000 mg/kg

i) STOT-repeated NOAEL Oral = 250 mg/kg

exposure

# Substance(s) listed on the IARC Monographs:

silica sand; quartz Group 1 bis-[4-(2,3-Group 3

epoxipropoxi)phenyl]propane

titanium dioxide; Dioxotitanium Group 2B

# Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

titanium dioxide; Dioxotitanium

### Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

titanium dioxide; Dioxotitanium

### Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

### 12. ECOLOGICAL INFORMATION

Print date 01/03/2024 KERAPOXY / A 10 Production Name Page n. 6 of

### **Toxicity**

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

### List of Eco-Toxicological properties of the product

The product is classified: Acute aguatic hazard, category 3(H402), Chronic (long term) aguatic hazard, category 3(H412)

### List of Eco-Toxicological properties of the components

Component Ident. Numb. **Ecotox Data** 

CAS: 14808-60- a) Aquatic acute toxicity: LC50 carp > 10000 mg/L 72h silica sand; quartz

7 - EINECS: 238-878-4

bis-[4-(2,3-CAS: 1675-54-3, a) Aquatic acute toxicity: LC50 Fish = 2 mg/L 96h

epoxipropoxi)phenyl]propane 25085-99-8 -

> EINECS: 216-823-5 - INDEX: 603-073-00-2

> > a) Aquatic acute toxicity: EC50 Daphnia = 1.8 mg/L 48h

alkyl epoxy resin; Oxirane,

mono((C12-14-alkyloxy)methyl) derivatives

CAS: 68609-97- a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96h 2 - FINECS:

271-846-8 -INDEX: 603-103-00-4

> a) Aquatic acute toxicity: EL50 Daphnia = 7.2 mg/L 48h a) Aquatic acute toxicity: EC50 Algae = 843 mg/L 72h

> b) Aquatic chronic toxicity: NOEC Algae = 500 mg/L 72h

formaldehyde, polymer with 2-CAS: 9003-36-5 a) Aquatic acute toxicity: LC50 Fish = 5.7 mg/L 96h

(chloromethyl)oxirane and phenol; - EINECS: 701-

263-0

a) Aquatic acute toxicity: EC50 Daphnia = 2.55 mg/L 48h a) Aquatic acute toxicity: EC50 Algae = 1.8 mg/L 72h

### Persistence and degradability

#### Persitence/Degradability: Component

alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives

Readily biodegradable

### Bioaccumulative potential

#### Component **Bioaccumulation**

alkyl epoxy resin; Oxirane,

mono((C12-14-alkyloxy)methyl)

derivatives

Not bioaccumulative

### Mobility in soil

N.A.

# Other adverse effects

NΔ

### 13. DISPOSAL CONSIDERATIONS

### **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Print date 01/03/2024 **Production Name** KERAPOXY / A 7 of Page n. 10 Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

### **UN** number

DOT-UN Number: Not Applicable ADR-UN number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

### **UN proper shipping name**

DOT-Proper Shipping Name: Not Applicable ADR-Shipping Name: Not Applicable IATA-Technical name: Not Applicable IMDG-Technical name: Not Applicable

### Transport hazard class(es)

DOT-Hazard Class: Not Applicable ADR-Class: Not Applicable IATA-Class: Not Applicable IMDG-Class: Not Applicable

# **Packing group**

DOT Packing Group: Not Applicable ADR-Packing Group: Not Applicable IATA-Packing group: Not Applicable IMDG-Packing group: Not Applicable

# **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

# Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

# **Special precautions**

Department of Transportation (DOT):

Not Applicable Road and Rail ( ADR-RID ) :

Not Applicable

Air (IATA):

Not Applicable

Sea ( IMDG ):

Not Applicable

# 15. REGULATORY INFORMATION

# **USA - Federal regulations**

### **TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

### **TSCA listed substances:**

silica sand; quartz is listed in TSCA Section 8b bis-[4-(2,3- is listed in TSCA Section 8b

epoxipropoxi)phenyl]propane

titanium dioxide; Dioxotitanium is listed in TSCA Section 8b alkyl epoxy resin; Oxirane, is listed in TSCA Section 8b

mono((C12-14-alkyloxy)methyl)

derivatives

formaldehyde, polymer with 2- is listed in TSCA Section 8b

(chloromethyl)oxirane and phenol;

Print date 01/03/2024 Production Name KERAPOXY / A Page n. 8 of 10

### **SARA - Superfund Amendments and Reauthorization Act**

### Section 302 - Extremely Hazardous Substances:

No substances listed

### Section 304 - Hazardous substances:

No substances listed

# Section 313 - Toxic chemical list:

No substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

# Substance(s) listed under CERCLA:

No substances listed

### CAA - Clean Air Act

### **CAA listed substances:**

No substances listed

### **CWA - Clean Water Act**

### **CWA listed substances:**

No substances listed

### **USA - State specific regulations**

### **California Proposition 65**

### Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen titanium dioxide; Dioxotitanium Listed as carcinogen

### Massachusetts Right to know

# Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

titanium dioxide; Dioxotitanium

### Pennsylvania Right to know

# Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz

titanium dioxide; Dioxotitanium

### **New Jersey Right to know**

# Substance(s) listed under New Jersey Right to know:

silica sand; quartz

titanium dioxide; Dioxotitanium

### Canada - Federal regulations

### **DSL - Domestic Substances List**

All the substances are listed in the DSL.

### **NDSL - Non Domestic Substances List**

This product complies with NDSL inventory

# **NPRI - National Pollutant Release Inventory**

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

### 16. OTHER INFORMATION

Safety Data Sheet dated: 12/14/2023 - version 8

### **Additional classification information**

NFPA Health: 1 = Slight

NFPA Flammability: 1 = Combustible if heated

NFPA Reactivity: 0 = MinimalNFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial,

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Print date 01/03/2024 Production Name KERAPOXY / A 9 of 10 Page n.

H319	Causes serious eye irritation.		
H350	May cause cancer.		
H351	Suspected of causing cancer.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H401	Toxic to aquatic life		
H411	Toxic to aquatic life with long lasting effects.		
Code	Hazard class and hazard category	Description	
A.2/2	Skin Irrit. 2	Skin irritation, Category 2	
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A	
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1	
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B	
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A	
A.6/2	Carc. 2	Carcinogenicity, Category 2	
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1	
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2	
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2	
Legend to abbreviations and acronyms used in the safety data sheet:			

# Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

**Description** 

Causes skin irritation.

May cause an allergic skin reaction.

Code H315

H317

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

### Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 01/03/2024 KERAPOXY / A 10of 10 Production Name Page n.