

## Safety Data Sheet

### PRIMER SN FAST PART A

Safety Data Sheet dated: 10/27/2022 - version 1

Date of first edition: 10/27/2022



## 1. IDENTIFICATION

### Product identifier

Mixture identification:

Trade name: PRIMER SN FAST PART A

Trade code: 9002147

### Recommended use of the chemical and restrictions on use

Recommended use: Primer

Restrictions on use: Not available

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888


Responsible: RDProductSafety@mapei.com

### Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION



### Classification of the chemical

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Skin Sensitization, Category 1B

May cause an allergic skin reaction.

Chronic (long term) aquatic hazard, category 2

Toxic to aquatic life with long lasting effects.

### Label elements

#### Hazard pictograms and Signal Word



Warning

### Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321	Specific treatment (see supplementary instructions on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container in accordance with applicable regulations.

**Ingredient(s) with unknown acute toxicity:**

None

**Hazards not otherwise classified identified during the classification process:**

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substances**

Not Relevant

**Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

**List of components**

Concentration (%)	Name	Ident. Numb.	Classification	Registration Number
50-75 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
25-50 %	bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin	CAS:25085-99-8 EC:600-013-7	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
5-10 %	phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol	CAS:28064-14-4 EC:608-164-0	Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 2, H411	N.A.
2.5-5 %	alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1, H317	
1-2.5 %	benzyl alcohol; benzenemethanol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2A, H319	

**4. FIRST AID MEASURES**

**Description of first aid measures**

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Obtain medical attention if skin related symptoms persist.
- Remove contaminated clothing immediately and dispose of safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

**Most important symptoms/effects, acute and delayed**

Eye irritation  
Eye damages  
Skin Irritation  
Erythema

**Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

---

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media**

Suitable extinguishing media:

Water.  
Carbon dioxide (CO2).

**Unsuitable extinguishing media:**

None in particular.

**Specific hazards arising from the chemical**

Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.  
Hazardous combustion products: Not available  
Explosive properties: Not available  
Oxidizing properties: Not available

**Special protective equipment and precautions for fire-fighters**

Use suitable breathing apparatus.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.  
Remove persons to safety.  
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
Limit leakages with earth or sand.

**Methods and material for containment and cleaning up**

Suitable material for taking up: absorbing material, organic, sand  
Retain contaminated washing water and dispose it.

---

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.  
Exercise the greatest care when handling or opening the container.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
See also section 8 for recommended protective equipment.

**Conditions for safe storage, including any incompatibilities**

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**List of components with OEL value**

	OEL Type	Country	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Note
silica sand; quartz CAS: 14808-60-7	ACGIH		0.025				A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
	MAK	AUSTRIA	0.15				
	MAK	SWITZERLAND	0.15				
benzyl alcohol; benzenemethanol CAS: 100-51-6	MAK	GERMANY	22	5			
	MAK	SWITZERLAND	22	5			

Appropriate engineering controls: Not available

#### Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0,35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0,5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluorinated rubber - FKM: thickness  $\geq 0,4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Liquid Beige

Odour: Characteristic

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 94 °C (201 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: No data available

Relative density: 1.58 g/cm<sup>3</sup>

Solubility in water: insoluble

Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available

Oxidizing properties: No data available

Solid/gas flammability: No data available

### Other information

Substance Groups relevant properties No data available

Miscibility: No data available

Fat Solubility: No data available

Conductivity: No data available

## 10. STABILITY AND REACTIVITY

**Reactivity**

Stable under normal conditions

**Chemical stability**

Data not available.

**Possibility of hazardous reactions**

None.

**Conditions to avoid**

Stable under normal conditions.

**Incompatible materials**

None in particular.

**Hazardous decomposition products**

None.

**11. TOXICOLOGICAL INFORMATION****Information on toxicological effects****Toxicological information of the product:**

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin irritation, Category 2(H315)
c) serious eye damage/irritation	The product is classified: Eye irritation, Category 2A(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sensitization, Category 1B(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

**Toxicological information of the main substances found in the product:**

silica sand; quartz	a) acute toxicity	LD50 Oral Rat = 500 mg/kg
phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol	a) acute toxicity	LD50 Skin Rabbit > 5000 mg/kg
		LD50 Oral Rat > 11400 mg/kg
alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives	a) acute toxicity	LD50 Skin Rabbit > 3987 mg/kg
		LD50 Oral Rat = 17100 mg/kg
benzyl alcohol; benzenemethanol	a) acute toxicity	LD50 Skin Rabbit = 2000 mg/kg
		LC50 Inhalation Rat = 8.8 mg/l 4h
		LD50 Oral Rat = 1230 mg/kg
		LD50 Skin Rabbit = 2 g/kg
		LD50 Oral Rat = 1230 mg/kg

**Substance(s) listed on the IARC Monographs:**

silica sand; quartz Group 1

**Substance(s) listed as OSHA Carcinogen(s):**

silica sand; quartz

**Substance(s) listed as NIOSH Carcinogen(s):**

silica sand; quartz

**Substance(s) listed on the NTP report on Carcinogens:**

silica sand; quartz

**12. ECOLOGICAL INFORMATION****Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

**List of Eco-Toxicological properties of the product**

The product is classified: Chronic (long term) aquatic hazard, category 2(H411)

**List of components with eco-toxicological properties**

Component	Ident. Numb.	Ecotox Infos
silica sand; quartz	CAS: 14808-60-7 - EINECS: 238-878-4	a) Aquatic acute toxicity : LC50 carp > 10000 mg/L 72h
benzyl alcohol; benzenemethanol	CAS: 100-51-6 - EINECS: 202-859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 460 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 10 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia water flea = 23 mg/L 48h

**Persistence and degradability**

Not available

**Bioaccumulative potential**

Not available

**Mobility in soil**

Not available

**Other adverse effects**

Not available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

### UN number

DOT-UN Number: UN3082

ADR-UN number: 3082

IATA-Un number: 3082

IMDG-Un number: 3082

### UN proper shipping name

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin - phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin - phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin - phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin - phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol)

### Transport hazard class(es)

DOT-Hazard Class: 9

ADR-Class: 9

IATA-Class: 9

IMDG-Class: 9

### Packing group

DOT-Packing group: III

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

### Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335, IB3, T4, TP1, TP29

DOT-Label(s): 9

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A

DOT-Non-Bulk: N/A

Road and Rail (ADR-RID) :

ADR exempt: No

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA) :

IATA-Passenger Aircraft: 964

IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisioning: A97 A158 A197

Sea (IMDG) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

## 15. REGULATORY INFORMATION

### USA - Federal regulations

#### TSCA - Toxic Substances Control Act

##### TSCA inventory:

All the components are listed on the TSCA inventory

##### TSCA listed substances:

silica sand; quartz is listed in TSCA Section 8b

bisphenol a epoxy resin; 1-Chloro-4 Trifluoromethyl Bisphenol A Epoxy Resin is listed in TSCA Section 8b

phenol, polymer with formaldehyde, glycidyl ether; 2-(chloromethyl)oxirane; Formaldehyde; Phenol is listed in TSCA Section 8b

alkyl epoxy resin; Oxirane, mono((C12-14-alkyloxy)methyl) derivatives is listed in TSCA Section 8b

benzyl alcohol; benzenemethanol is listed in TSCA Section 8b

#### SARA - Superfund Amendments and Reauthorization Act

##### Section 302 - Extremely Hazardous Substances:

No substances listed

##### Section 304 - Hazardous substances:

No substances listed

##### Section 313 - Toxic chemical list:

No substances listed

#### CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

##### Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

##### CAA listed substances:

benzyl alcohol; benzenemethanol is listed in CAA Section 112(b) - HON

#### CWA - Clean Water Act

##### CWA listed substances:

No substances listed

### USA - State specific regulations

#### California Proposition 65

##### Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen

#### Massachusetts Right to know

##### Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

benzyl alcohol; benzenemethanol

#### Pennsylvania Right to know

##### Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz

benzyl alcohol; benzenemethanol

#### New Jersey Right to know

##### Substance(s) listed under New Jersey Right to know:

silica sand; quartz

## Canada - Federal regulations

### DSL - Domestic Substances List

#### DSL (Domestic Substances List)

All the substances are listed in the DSL.

### NDSL - Non Domestic Substances List

#### NDSL (Non Domestic Substances List)

No substances listed

### NPRI - National Pollutant Release Inventory

#### NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

## 16. OTHER INFORMATION

Safety Data Sheet dated: 10/27/2022 - version 1

### Additional classification information

NFPA Health: 1 = Slight

NFPA Flammability: 1 = Combustible if heated

NFPA Reactivity: 0 = Minimal

NFPA Special Risk: NONE



NFPA

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

### Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
WGK: German Water Hazard Class.  
KSt: Explosion coefficient.