

Light Reflectivity

2.5 mm LVT with Diamond 10® Technology
Biome™

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g. 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°:0° or 0°:45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values great than 25% can contribute to the LEED® Interior Lighting Credit.

Value	Sku Numbers
0-9	ST133
10-14	ST132, ST152, ST265, ST275, ST274
15-19	ST150, ST255, ST264, ST273, ST285
20-24	ST151, ST154, ST253, ST262, ST263, ST293, ST294
25-29	ST131, ST251, ST254, ST272, ST283, ST295
30-34	ST284, ST291
35-39	ST155, ST250, ST252, ST261, ST271
40-44	--
45-49	ST270, ST292
50-54	ST260, ST281, ST282, ST290
55-59	--
60-64	ST280
65-69	--
70-74	--