

Light Reflectivity

3.2 mm LVT with Diamond 10® Technology
Natural Creations®

All light reflectivity values listed are based on a percentage system, the higher the percentage (e.g. 20-24, 35-39), the higher the light reflectance of the floor. It is measured per ASTM E1349, *Standard Test Method for Reflectance Factor and Color by Spectrophotometry Using Bidirectional (45°:0° or 0°:45°) Geometry*. Research indicates reflectance can help drive daylight further into space and reduce reliance on artificial lighting, resulting in reduced electricity usage and costs. Glare from flooring is a characteristic of glossy finishes, not reflectance. Flooring in lighter colors with a matte finish have high reflectance values, but do not add to glare. Flooring with light reflectivity values great than 25% can contribute to the LEED® Interior Lighting Credit.

Value	Skus Numbers
0-9	NA163, NA182, NA313, NA503, NA507
10-14	NA192, NA225, NA237, NA333, NA501, NA502, NA505, NA506
15-19	NA120, NA121, NA143, NA191, NA194, NA236
20-24	NA122, NA142, NA161, NA180, NA181, NA193, NA228, NA332, NA504
25-29	NA144, NA171, NA172, NA331, NA342, NA343, NA367
30-34	NA190, NA235, NA311, NA312, NA352, NA366
35-39	NA123, NA141, NA226, NA227, NA365, NA508
40-44	NA184, NA340, NA341, NA351, NA509
45-49	NA170, NA183, NA310, NA330, NA500, NA401, NA403, NA408
50-54	NA160, NA350, NA400, NA404, NA406, NA405, NA407
55-59	--
60-64	--
65-69	--
70-74	--