

PRO951

PREMIUM WALL BASE ADHESIVE



1. PRODUCT NAME

Prosol® PRO951 Premium Wall Base Adhesive

2. MANUFACTURER

Prosol
4305 Griffith St.
Saint Laurent QC, H4T 2A2
Prosol.ca
514-745-1212

3. DESCRIPTION

PRO951 is a maximum performance, fast-tack adhesive formulated for the interior installation of rubber, vinyl and carpet wall base. Superior wet-suction capabilities ensure a tenacious bond over porous wall surfaces including gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete. Tenacious green grab keeps corners wrapped tight, rated for interior residential and commercial use. VOC < 1 g/L.

FEATURES & BENEFITS

- Non-staining formula with superior green grab to keep corners wrapped tight
- Rapid set-up for fast, easy installation
- Strong initial grab for holding wall base
- Enviro-Friendly – solvent-free and LEED® compliant; VOC 11 g/L, SCAQMD Rule 1168
- Bonds with gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete
- Coverage (per 28.7 oz. / 849 mL cartridge): 1/4" bead - 56 lineal feet
3/8" bead - 35 lineal feet

PRO951 is a solvent free, acrylic latex adhesive that meets the strict requirements of the South Coast Air Quality Management District and may contribute one LEED point for "Low-Emitting Material-Adhesive and Sealant" (IEQ Credit 4.1) and "Low-Emitting Materials-Flooring Systems" (IEQ Credit 4.3). This product may also contribute to LEED points for MR Credit 5. Visit usgbc.org for additional details.

USES

For the interior installation of vinyl wall base, rubber wall base and carpet wall base

SUBSTRATES: Gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete. For floorings and backings not listed, contact Technical Services at 514-745-1212 or visit www.prosol.ca.

LIMITATIONS

- For interior installations only .
- Not recommended over non-porous materials or painted surfaces .
- Concrete and plaster must be properly seasoned and dry prior to installation .

Recommended Coverage Rate*

POROUS SUBSTRATES:

2.3 or 5-Hole Applicator Nozzle

Coverage / Couverture:
70 linear ft/per30 oz. (21.3 m/per 887mL)

**The trowel notches referenced are those typically recommended for the type of flooring being installed and are shown as a guide. Consult flooring manufacturer for their specific trowel recommendations.*



PRO951

PREMIUM WALL BASE ADHESIVE



4. TECHNICAL DATA

Product Type:	Acrylic Polymer Paste
Color:	Tan
Odor:	Mild, sweet odor, odorless when dry
Open Time:	Up to 10 minutes
Working Time:	Up to 30 minutes
Shelf Life:	1 year in original unopened container in a controlled environment
Storage:	Protect from freezing. Does not require thinning.
VOC:	< 1 g/L

5. INSTRUCTION

PREPARATION:

30 oz. cartridge – Unscrew cap, cut top seal and load into closed barrel gun or open barrel skeleton gun. Squeeze gun gently, with even pressure, to apply.

Surfaces must be clean, dry and free of contaminants including paint. If the back of the wall base is soiled prior to installation, clean with a cloth dampened with a mild soap and water solution, rinse and dry.

INSTALLATION:

Maintain a consistent and ambient relative humidity before, during and after installation (between 65-85° F with a maximum RH of 65%). Follow the wall base manufacturer's guidelines for layout and design. Apply adhesive to the back of the wall base with appropriate applicator or 1/8" notch trowel to ensure 90% coverage of adhesive, while not spreading within 1/4" from the top of the wall base. Observe the appropriate open time. While the adhesive is still fresh, press the wall base firmly in place. Be careful not to stretch the wall base during the application process. Use a hand roller to ensure a secure and void-free bond between the wall base and the substrate. Roll the wall base in the direction of the last piece installed to ensure a tight seam.

CLEAN UP:

Fresh adhesive – warm, soapy water with a clean white cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth.

6. AVAILABILITY

Packaging
PRO951-C 849 mL Tube (772928121333)

7. WARRANTY

Prosol distribution offers a limited-product warranty on this product when installed in accordance with the printed specifications. Ask your sales representative, visit www.prosol.ca or call (514-745-1212) for a copy of the warranty.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at 514-745-1212 or visit www.prosol.ca.

10. FILING SYSTEM

Division 9

