

Stringers & Risers

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Stair Stringers and Risers.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Rubber Stringers and Risers are manufactured from a proprietary thermoplastic rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861, Type TP, Group 1 (solid) Standard Specification for Resilient Wall Base.

Tarkett Vinyl Stringers and Risers are formulated from a homogeneous polyvinyl chloride composition combined with high quality additives and colorants designed specifically to meet the performance and dimensional requirements of ASTM F-1861-98, Type TV, Group 1 (solid) Standard Specification for Resilient Wall Base.

1.3.2. **Styles:**

Stringers	Risers
RS-XX (Rubber)	RR-XX (Rubber)
VS-XX (Vinyl)	VR-XX (Vinyl)

1.3.3. **Physical Characteristics:**

Rubber Stringers (RS-XX):

Thickness: 0.080" (2 mm)
10" (25.4 cm) height x 6 ft. (1.83 cm) length

Vinyl Stringers (VS-X):

Thickness: 0.080" (2 mm)
10" (25.4 cm) height x 50 ft. (15.24 m) length

Rubber Riser (RR):

Thickness: 1/8" (3.17 cm)
6" (15.24 cm) high x 4' (1.22 m) length
6" (15.24 cm) high x 100' (30.48 m) length
7" (17.78 cm) high x 4' (1.22 m) length
7" (17.78 cm) high x 5' (1.52 m) length
7" (17.78 cm) high x 6' (1.83 m) length
7" (17.78 cm) high x 50' (15.24 m) length

Vinyl Riser (VR):

Thickness: .080" (2 mm)
Sizes: 6" (15.24 cm) high x 4' (1.22 m) length
6" (15.24 cm) high x 120' (36.58 m) length
7" (17.78 cm) high x 4' (1.22 m) length
7" (17.78 cm) high x 50' (15.24 m) length

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Flexibility:** Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.35 mm) diameter cylinder.

2.2. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.

2.3. **Fire Resistance:**

ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1
ASTM E 662/NFPA 258 (Smoke Density) - less than 450

2.4. **CAN/ULC S102.2:**

Vinyl: FSR 140 / SDV 330

Rubber: FSR 165 / SDV 345

3. INSTALLATION

See Stringers and Riser installation & maintenance instructions for complete details.

3.1. **Adhesives:**

	Tarkett 960 Cove Base	Tarkett 946 Premium Contact
Application	(Porous Only) 1/8" x 1/8" x 1/8" SQ notch	Brush or roller
Approx. Coverage Per Gal.	6" – 125 to 175 lf. 7" – 105 to 155 lf. 10" – 65 to 115 lf.	6" – 144-215 lf. 7" – 123-184 lf. 10" – 86-129 lf.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to the Stair Stringers and Riser instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com

Contact Technical Support at (800) 899-8916 or E-mail:

Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com