



Calfeutrante acrylique de qualité supérieure

DS-6257F-1024

**Globally Proven
Construction Solutions**



1. NOM DU PRODUIT

Calfeutrante acrylique de qualité supérieure

2. FABRICANT

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 États-Unis

Téléphone: +1.203.393.0010, poste 1235

Numéro sans frais: 1.800.243.4788, poste 1235

Télécopieur: +1.203.393.1684

Site Web: laticrete.com

3. DESCRIPTION DU PRODUIT

Premium Acrylic Caulk is a high performance siliconized acrylic latex sealant designed for interior applications for ceramic tile and stone. Premium Acrylic Caulk is ideal for a variety of caulking applications in bathrooms, kitchens and floors.

Utilisation

- For caulking around sinks, tubs and showers
- Great for sealing joints between countertop and backsplashes
- Corner joints where walls meet

Avantages

- Resists mold & mildew growth
- Stain resistant
- Matches all 40 LATICRETE® grout colors
- Easy to smooth and tool
- Adheres well to plumbing fixtures
- Resistant to staining and cracking
- Flexible

Supports Appropriés

Conditionnement

Tubes 10,5 oz (310 ml)

Couverture approximative

- Coverage will vary depending upon joint size and width. Consult LATICRETE Technical Services for exact coverage.
- Approximately 25 lineal feet (7.62 m) per tube at 1/4" x 1/4" (6 x 6 mm) joint width.

Restrictions

- For interior use only.
- Not for submerged and or permanent wet area applications. Use LATASIL™.
- Sealants are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane (see Section 10 FILING SYSTEMS).
- For sensitive porous substrates such as limestone and sandstone, test sealant on a small area for any indication of fluid migration prior to job commencement.
- Not for joint applications where physical abuse or abrasion is likely.
- Not a structural glazing adhesive.
- Joint width should not exceed 1/2" (12.77 mm) thickness and no thinner than 1/8" (3.2 mm).
- For perimeter sealing or expansion joint design, the ratio of the joint width to sealant depth should be no greater than 2 times the width than depth.

Mises en garde

- Protect finished work from traffic until fully cured.
- Uncured sealant causes skin irritation and serious eye damage. Avoid contact with sealant until cured. Wash thoroughly after handling.
- KEEP OUT OF REACH OF CHILDREN.
- Check with SDS sheet for further cautions.

4. DONNÉES TECHNIQUES

Propriétés physiques

Service Temperature Range	Unsanded -20°F (-28°C) to 180°F (82°C) Sanded 0°F (-17°C) to 180°F (82°C)
Application Temperature Range	40°F (4°C)–90°F (32°C)
Open Time	10–20 Minutes
Set Time	48 Hours
Full Cure	2 Weeks
Clean Up	Soapy Water
Mildew Resistance	Good
Consistency	Non-sag

Caractéristiques sous réserve de modification sans préavis. Les résultats présentés sont typiques, mais ils reflètent les procédures d'essai utilisées. Les performances réelles sur le terrain dépendent des méthodes de pose et des conditions locales.

5. POSE

• Preparation

- Clean all joints and glazing pockets, removing all foreign matter and contaminants such as grease, oil, dust, water, frost, surface dirt, old sealants and protective coatings.
- In all cases where utilized, solvents should be wiped on and off with clean, oil and lint free cloths.
- When using any cleaning solvent always follow solvent manufacturer's safety and handling recommendations.
- For stone, or agglomerate tile test small area to check for any fluid migration.

Application

General installation instructions:

- Apply masking tape to the face of the veneer to protect it from the sealant. Masking tape will allow for easier removal of sealant if any comes into contact with the face of the tile. Sealant should only be applied into the joints, adhering on the flanks of the veneer. Applying the masking tape results in a cleaner look and allows for easy tooling without spillage onto the face of the veneer.
- Apply sealant to the joint, filling completely.
- "Tool" when complete (within 5–7 minutes) for a smooth professional finish.
- Remove masking tape immediately after tooling. Wipe any sealant off the face of the stone immediately.

6. DISPONIBILITÉ ET COÛT

Disponibilité

Les produits LATICRETE® et LATAPOXY® sont proposés dans le monde entier.

Appeler un des numéros suivants pour obtenir des informations relatives aux distributeurs:

Numéro sans frais: 1.800.243.4788

Téléphone: +1.203.393.0010

Pour obtenir de l'information en ligne de distributeurs, visiter LATICRETE à l'adresse suivante laticrete.com

Coût

Communiquez avec le distributeur LATICRETE le plus proche.

7. GARANTIE

Voir 10. SYSTÈME DE CLASSIFICATION:

- 1 Year Product Warranty (US) (English)

8. ENTRETIEN

Joints should be cleaned regularly with common cleaners on a regular basis.

9. SERVICES TECHNIQUES

Soutien technique

Pour tout renseignement, appeler la ligne d'aide du service technique de LATICRETE:

Numéro sans frais: 1.800.243.4788, ext. 1235

Téléphone: +1.203.393.0010, ext. 1235

Télécopieur: +1.203.393.1948

Documentation technique et de sécurité

Pour obtenir la documentation technique et les consignes de sécurité, visiter notre site Web à laticrete.com.

10. SYSTÈME DE CLASSIFICATION

Des informations supplémentaires sur les produits sont disponibles sur notre site Web à laticrete.com. Liste des documents connexes:

- DS 230.13: LATICRETE Product Warranty (United States and Canada)
- DS 236.0: 9235 Waterproofing Membrane
- DS 663.0: HYDRO BAN®
- DS 6200.1: LATASIL™

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.