Benefits

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

Budget-friendly

Water-resistant – 72-hour spill protection Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have

reduced exposure to formaldehyde vapors an

Performant and durable construction BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards

Heavy commercial abrasion resistance

Water-resistant laminate that can be installed in kitchens and half bathrooms

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains Water-resistant – 72-hour spill protection

Easy and versatile Installation Floating installation

2 in 1 - comes with an attached underlayment Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Matching moldings available

Can be installed on all floor levels, even on walls

Quiet and comfortable Foam backing for greater temperature and sound insulation

Notable look Wide and long planks

Mat finish

Best-in-class Warranty No Questions Asked Replacement

Quickship Stock product for faster delivery

Collection Bulletin page 1 of 4

Product Specifications

Market Segments Hospitality, Pro, Residential, Workspace

Brand HydraPlanks
Sub Category Water-Resistant

CollectionLittoraConstructionLaminateFormatPlank

Abrasion Resistance AC5 Class 33: Heavy Commercial Use

Species Oak

 Width
 7.68" (195 mm)

 Total Thickness
 0.563" (14.3 mm)

Edges4-Sided Micro Bevel & WaxLocking SystemVälinge 5G: Drop LockFinishRegistered EmbossedTop SurfaceAluminum Oxide

Gloss Mat
Pattern Repeat 6
IIC 63
STC 62
Underlay true

 $\begin{tabular}{lll} Formaldehyde & TSCA Title VI \\ Length & 47.835" \, (1215 \ mm) \end{tabular}$

Certifications FloorScore, BLC Certification, QuickShip, TSCA Title VI

Compliant

Installation Methods Floating, Compatible with embedded radiant heating

☑ Laminate Installation Guide (Drop Lock)

Laminate Installation Video - Välinge 5G Locking System

Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use No Questions Asked Replacement Mininum 30 days

Fade *Lifetime*Wear *Lifetime*Stain *Lifetime*

Manufacturing Defects Lifetime

Commercial use Wear 15 Years

Stain 15 Years

Manufacturing Defects 15 Years

Fade 15 Years

Collection Bulletin page 2 of 4

Packaging information

Units Per Box 6 **Boxes Per Pallet** 55

Box Weight 40.54 Pounds (18390.89 Grams)

Square Meters Per Box 78.18 **Square Meters Per Pallet Square Feet Per Box** 15.3 **Square Feet Per Pallet** 841.5

Moldings





Matching 94.488" X 0.945" X 2.834" (2400 mm X 24 mm X 72 mm)



Matching 94.488" X 0.671" X 1.771" (2400 mm X 17 mm X 45 mm)



T-Molding Matching 94.488" X 0.551" X 1.771" (2400 mm X 14 mm X 45 mm)

Styles offered



#1445 (Plank) Abyssal Registered Embossed



#1446 (Plank)
Coralline
Registered Embossed



#1447 (Plank)
Cormorant
Registered Embossed



#1448 (Plank) Loch Registered Embossed



#1449 (Plank)Nautilus
Registered Embossed



#1450 (Plank) Shoreline Registered Embossed