

Maven Laminate

Benefits

Family friendly (including pet)

Easy to clean
Stain resistant, including pet stains
Budget-friendly
Ultra-durable and scratch-resistant surface

Safe and healthy

FloorScore® Certified for compliance with rigorous indoor air quality requirements
TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have reduced exposure to formaldehyde vapors and

Performant and durable construction

Commercial abrasion resistance
BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards
Ultra-durable and scratch-resistant surface

Easy maintenance

Easy to clean
Stain resistant, including pet stains

Easy and versatile Installation

Floating installation
Compatible with embedded radiant heating
No telegraphing, even when installed over hard surface flooring
Matching moldings available
Can be installed on all floor levels, even on walls

Notable look

Wide and long planks
Mat finish

Best-in-class Warranty

No Questions Asked Replacement

Quickship

Stock product for faster delivery

Maven Laminate

Product Specifications

Market Segments	Builder, Pro, Residential
Brand	PrimaPlanks
Sub Category	Regular
Collection	Maven
Construction	Laminate
Format	Plank
Abrasion Resistance	AC4 Class 32: General Commercial Use
Species	Oak
Width	7.717" (196 mm)
Total Thickness	0.484" (12.3 mm)
Edges	4-Sided Micro Bevel
Locking System	Välinge 2G: Drop Lock
Finish	Embossed
Top Surface	Aluminum Oxide
Gloss	Mat
Pattern Repeat	6
IIC	n/a
STC	n/a
Underlay	false
Formaldehyde	TSCA Title VI
Length	47.87" (1216 mm)
Certifications	FloorScore, BLC Certification, QuickShip, TSCA Title VI Compliant
Installation Methods	Floating, Compatible with embedded radiant heating 🔗 Laminate Installation Guide (Drop Lock) 🔗 Wall Installation Guide - Laminate 🔗 Laminate Installation Video - Välinge 2G "Drop Lock" Locking System

Warranties

- [🔗 Laminate Warranty Guide](#)
- [🔗 Laminate Maintenance Guide](#)

Residential use	No Questions Asked Replacement <i>Minimum 30 days</i> Wear <i>Lifetime</i> Stain <i>Lifetime</i> Manufacturing Defects <i>Lifetime</i> Fade <i>Lifetime</i>
Commercial use	Manufacturing Defects <i>5 Years</i> Wear <i>5 Years</i> Stain <i>5 Years</i> Fade <i>5 Years</i>
Light commercial use	Manufacturing Defects <i>15 Years</i> Wear <i>15 Years</i> Stain <i>15 Years</i> Fade <i>15 Years</i>

Maven Laminate

Packaging information

Units Per Box	6
Boxes Per Pallet	65
Box Weight	33.86 Pounds (15357.72 Grams)
Square Meters Per Box	1.43
Square Meters Per Pallet	92.93
Square Feet Per Box	15.39
Square Feet Per Pallet	1000.35

Moldings



T-Molding

Matching

94.488" X 0.551" X 1.771"
(2400 mm X 14 mm X 45 mm)



Square Nose

Matching

94.488" X 0.591" X 1.377"
(2400 mm X 15 mm X 35 mm)



Reducer

Matching

94.488" X 0.591" X 1.771"
(2400 mm X 15 mm X 45 mm)



Flushmount Stair Nose - Round

Matching

94.488" X 0.945" X 2.834"
(2400 mm X 24 mm X 72 mm)



Stair Nose Mdf

Matching

94.488" X 0.709" X 2.165"
(2400 mm X 18 mm X 55 mm)

Maven Laminate

Styles offered



#1720 (Plank)
Anderson
Embossed



#1721 (Plank)
Anning
Embossed




#1722 (Plank)
Carson
Embossed



#1723 (Plank)
Edison
Embossed



#1724 (Plank)
Franklin
Embossed



#1725 (Plank)
Goodall
Embossed



#1726 (Plank)
Gutenberg
Embossed



#1727 (Plank)
Hawking
Embossed



#1728 (Plank)
Hodgkin
Embossed



#1729 (Plank)
Hopper
Embossed



#1730 (Plank)
Johnson
Embossed



#1731 (Plank)
Wallace
Embossed