#### **Benefits**

Family friendly (including pet) Easy to clean

Stain resistant, including pet stains

Budget-friendly

Ultra-durable and scratch-resistant surface

Safe and healthy FloorScore® Certified for compliance with rigorous indoor air quality requirements

TSCA Title VI is a new standard of the Environmental Protection Agency (EPA) for allowable emissions from adhesives used in composite wood products. This certification ensures that certain wood products have

reduced exposure to formaldehyde vapors an

Performant and durable construction Commercial abrasion resistance

BLC Certified ® - Ensures that the floor covering you're buying surpasses industry quality standards

Ultra-durable and scratch-resistant surface

Easy maintenance Easy to clean

Stain resistant, including pet stains

Easy and versatile Installation Floating installation

Compatible with embedded radiant heating

No telegraphing, even when installed over hard surface flooring

Matching moldings available

Can be installed on all floor levels, even on walls

Notable look Wide and long planks

Mat finish

Best-in-class Warranty No Questions Asked Replacement

Quickship Stock product for faster delivery

Collection Bulletin page 1 of 4

## **Product Specifications**

Market Segments Builder, Pro, Residential

BrandPrimaPlanksSub CategoryRegularCollectionGalloConstructionLaminateFormatPlank

Abrasion Resistance AC4 Class 32: General Commercial Use

**Species** Oak

Width7.68" (195 mm)Total Thickness0.327" (8.3 mm)Edges4-Sided Micro BevelLocking SystemVälinge 2G: Drop Lock

Finish Embossed
Top Surface Aluminum Oxide

Gloss Mat
Pattern Repeat 6
IIC n/a
STC n/a
Underlay false

Formaldehyde TSCA Title VI Length 47.835" (1215 mm)

Certifications FloorScore, BLC Certification, QuickShip, TSCA Title VI

Compliant

**Installation Methods** Floating, Compatible with embedded radiant heating

 $\square$  Laminate Installation Guide (Drop Lock)

☑ Wall Installation Guide - Laminate

Laminate Installation Video - Välinge 2G "Drop

Lock" Locking System

#### Warranties

☑ Laminate Warranty Guide

☑ Laminate Maintenance Guide

Residential use No Questions Asked Replacement *Mininum 30 days* 

Wear *Lifetime* Stain *Lifetime* 

Manufacturing Defects Lifetime

Fade *Lifetime* 

Commercial use Fade 5 Years

Wear *5 Years* Stain *5 Years* 

Manufacturing Defects 5 Years

Light commercial use Fade 15 Years

Wear 15 Years Stain 15 Years

Manufacturing Defects 15 Years



Collection Bulletin page 2 of 4

# Packaging information

Units Per Box 8
Boxes Per Pallet 70

**Box Weight** 37.74 Pounds (17118.56 Grams)

Square Meters Per Box1.90Square Meters Per Pallet132.66Square Feet Per Box20.4Square Feet Per Pallet1428

# Moldings







 Flushmount Stair Nose - Round
 Reducer

 Matching
 Matching

 94.488" X 0.945" X 2.834"
 94.488" X

 (2400 mm X 24 mm X 72 mm)
 (2400 mm

Matching 94.488" X 0.433" X 1.771" (2400 mm X 11 mm X 45 mm) **T-Molding**Matching
94.488" X 0.394" X 1.771"
(2400 mm X 10 mm X 45 mm)

Collection Bulletin page 3 of 4

# Styles offered



#8050 (Plank) Agostino Embossed



#8051 (Plank) Alboro Embossed



#8052 (Plank) Armoric Embossed



#8053 (Plank) Arzon Embossed



#8054 (Plank) Castello Embossed



#8055 (Plank) Gaelic Embossed



#8056 (Plank) Gondola Embossed



#8057 (Plank)
Hermine
Embossed



#8058 (Plank) Malo Embossed



#8059 (Plank) Renzo Embossed



#8060 (Plank) Rialto Embossed



#8061 (Plank) Vaporetti Embossed